

DESOTO, INC -- SUPER DESOTHANE ACTIVATOR 910T211 -- 8010-00-330-7704

===== Product Identification =====

Product ID: SUPER DESOTHANE ACTIVATOR 910T211

MSDS Date: 09/15/1988

FSC: 8010

NIIN: 00-330-7704

MSDS Number: BBLQX

=== Responsible Party ===

Company Name: DESOTO, INC

Address: 1700 S. MOUNT PROSPECT

Box: 5030

City: DES PLAINES

State: IL

ZIP: 60017

Info Phone Num: (312) 391-9000

Emergency Phone Num: (312) 3

91-9000

Preparer's Name: SHERRIE M. STEVENSON

CAGE: EO501

=== Contractor Identification ===

Company Name: DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE

Address: 1608 4TH ST

Box: City: BERKELEY

State: CA

ZIP: 94710

Country: US

Phone: 800-228-5635 / 800-424-9300 CHEMTREC

CAGE: 85570

Company Name: DESOTO, INC

Address: 1700 S. MOUNT PROSPECT RD.

Box: 5030

City: DES PLAINES

State: IL

ZIP: 60017

Phone: (312) 391-9000

CAGE: EO501

===== Composition/Information on Ingredients =====

Ingred Name: METHYL

ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 25.0%

Other REC Limits:590 MG/CUM

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction by Wt: 10.0%

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 10.0%

Other REC

Limits:100 PPM

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ALIPHATIC POLYISOCYANATE, HEXAMETHYLENE DIISOCYANATE
POLYMER (HDI POLYMER)

CAS:28182-81-2

RTECS #:NQ9170000

Other REC Limits:1 MG/CUM

OSHA PEL:NONE

ACGIH TLV:NONE

Ingred Name:1,6-DIISOCYANATOHEXANE (HEXAMETHYLENE DIISOCYANATE)

CAS:822-06-0

RTECS #:MO1740000

Fraction by Wt: 49F. STORE LARGE QUANTITIES IN

BLDGS DESIGNED/PROTECTED FOR STORAGE FLAMMABLE LIQUIDS. DO

N'T APPLY

TO HOT SURFACES. DON'T TAKE INTERNALLY.

Other Precautions:STORE IN TIGHTLY CLOSED CONTAINERS/PROTECT FROM MOISTURE/FOREIGN MATERIALS. ISOCYANATES REACT SLOWLY W/WATER TO FORM CO2 GAS WHICH CAN CAUSE CONTAINER TO EXPAND OR RUPTURE. DON'T CUT, PUNCTURE OR WELD ON OR NEAR DRUM.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN AREA WHERE TLVS MAY BE EXCEEDED OR IF SPRAY MIST IS PRESENT, USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION.

Ventilation:PROVIDE LOCAL EXHAUST/MECHANICAL VENTILATION TO KEEP AIR Evaporation Rate & Reference:(N-BU AC = 1): 1

Appearance and Odor:CLEAR LIQUID, SOLVENT ODOR.

Percent Volatiles by Volume:50%

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES CONTACT W/WATER, ALCOHOLS & AMINES.

Stability Condition to Avoid:HEAT, ELECTRICAL EQUIPMENT, SPARKS & FLAME. DON'T STORE >49C. PROTECT FROM MOISTURE & FOREIGN MATERIALS.

Ha
azardous Decomposition Products:CO, CO2, OXIDES OF NITROGEN & TRACES OF HCN & ISOCAYANATE MONOMER.

=====
===== Disposal Considerations =====

Waste Disposal Methods:WHEN DISPOSING OF THIS MATERIAL/ENSURE THAT IT'S PACKAGED/STORE/TRANSPORTED/IN ACCORDANCE W/LOCAL, STATE/FEDERAL REGS. NO DISPOSAL METHOD IS TO BE USED THAT WOULD POSE AN ENVIRONMENTAL OR HUMAN HEALTH THREAT/ANY WHICH WOULD CONTAMINATED SURFACE WATER

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.