View NSN Online: https://aerobasegroup.gr/nsn/6850-00-003-5295

CHEMTRONICS INC -- CLEANING AND LUBRICATING COMPOUND -- 6850-00-003-5295

======== Product Identification ============

Product ID:CLEANING AND LUBRICATING COMPOUND

MSDS Date:09/18/1990

FSC:6850

NIIN:00-003-5295

MSDS Number: BCTYQ === Responsible Party ===

Company Name: CHEMTRONICS INC Address: 8125 COBB CENTER DRIVE

City:KENNESAW

State:GA ZIP:30144 Country:US

Info Phone Num:404-424-4888 FAX 404-424-4267

Emerg

ency Phone Num:404-424-4888/800-424-9300(CHEMTREC)

Preparer's Name: MICHAEL WATKINS

CAGE:2M589

=== Contractor Identification ===

Company Name: CHEMTRONICS INC Address: 8125 COBB CENTER DRIVE

Box:City:KENNESAW

State:GA ZIP:30152 Country:US

Phone:770-424-4888/800-645-5244

CAGE:21267

Company Name: CHEMTRONICS INC (CANCELLED USE 21267)

City:HAUPPAUGE

State:NY ZIP:11760 Country:US CAGE:2M589

Company Name: MALTER INTERNATIONAL BULK CHEMICAL DIVISION

Address:80 FIRST STREET

Box:City:GRETNA

State:LA ZIP:7005

Country:US

Phone:504-362-3232, OR 800-535-4095

CAGE:27978

======= Composition/Information on Ingredients ========

Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA

III)

CAS:76-13-1

RTECS #:KJ4000000 Fraction by Wt: 97%

Other REC Limits:NONE SPECIFIED OSHA PEL:1000PPM/1250STEL ACGIH TLV:1000PPM/1250STEL9192

Ozone Depleting Chemical:1

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000 Fraction by Wt: 35%

Other REC Limits: NONE SPEC

IFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1

Ingred Name: SILICON FLUID

CAS:63148-62-9 RTECS #:JT6485000 Fraction by Wt: 5%

Other REC Limits: NONE SPECIFIED

========= Hazards Identification =============

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >10,000 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUC

T IS IRRITATING TO BODY TISSUES, IT IS A CENTRAL NERVOUS SYSTEM DEPRESSANT, CAUSING NAUSEA AND DIZZINESS. CHRONIC SKIN EXPOSURE MAY CAUSE DERMATITIS. IT HAS A LOW TOXICITY. Explanation of Carcinogenicity: THE PRODUCT CONTAINS NO INGREDIENT THAT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN. Effects of Overexposure: HEADACHE, DIZZINESS, DROWSINESS, NAUSEA, STUPOR OR DULLNESS, LETHARGY AND DRUNKENNESS. VERY HIGH CONCENTRATIONS MAY LEAD TO UNCONSCIOUSNESS OR EVEN DEATH IN CON-FINED OR POORLY VENTILATED AREAS. REPEA TED SKIN CONTAC CAUSES REDDNESS. EYE CONTACT CAUSES DISCOMFORT. Medical Cond Aggravated by Exposure: CARDIOVASCULSR DISEASE. First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:D O NOT INDUCE VOMITING. GIVE 2 LAR **GE GLASSES** OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE, SEE A DOCTOR. Flash Point: NON-FLAMMABLE Extinguishing Media: PRODUCT IS NON FLAMMABLE. EXTINGUISH FIRE WITH MEDIA APPROPRIATE FOR SOURCE OF FIRE. Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. **USE WATER** SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard: CONTENTS UNDER PRESSURE! EXPOSURE TO TEMPERATURES OVER 130 F MAY RESULT IN RUPTURE OF THE CONTAINER.

======== Accidental Release Measures =============

Spill Release Procedures: SMALL SPILL: WIPE UP WITH RAGS OR TOWELS.

SEWER OR WATERWAY.

Neutralizing Agent:NONE

VENTILATE AREA. RESIDUE WILL EVAPORATE QUICKLY. DO NOT FLUSH TO

Handling and Storage Precautions:STORE BELOW 130 F. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE. DEPRESSURIZE BEFORE DISPOSAL. ROTATE STOCK.

Other Precautions: VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS. DO NOT ENTER WHERE VAPORS ARE SUSPECTED WITHOUT SELF CONTAINED BREATHING APPARATUS AND AN OBSERVER.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: USE NIOSH/MSHA APPROVED AIR SUPPLIED RES PIRATOR

OR RESPIRATOR FOR ORGANIC VAPOR IF EXPOSURE IS ABOVE THE TLV/PEL. IF EXPOSED ABOVE 1000 PPM USE ONLY A SUPPLIED AIR RESPIRATOR. SEE 29 CFR 1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE

Ventilation: NORMAL ROOM VENTILATION IS SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST IF PEL/TLV IS EXCEEDED.

Protective Gloves: NEOPRENE, PVA GLOVES RECOMMENDED.

Eye Protection: SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment: APRON AND WORK CLOTHING TO MINIMIZE EXPOSURE.

EYE WASH STATION & SAFETY SHOWER RECOMMENDED.

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

CHEMICAL NAME &

SYNONYMS-DICHLORODIFLUOROMETHANE-TRICHLOROTRIFLUOROETHANE;POLY(DIME THYL) SILOXANE

========= Physical/Chemical Properties =============

HCC:V2

NRC/State Lic Num: NOT RELEVANT

Boiling Pt:B.P. Text:118F,48C

Vapor Pres:334 MM Vapor Density:6.5

Spec G ravity:1.57

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE = 1)

Solubility in Water: NEGLIGIBLE

Appearance and Odor: COLORLESS LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:100

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

ALKALI AND ALKALINE EARTH METALS, POWDERED REACTIVE METALS SUCH AS AL, ZN, BE, STRONG BASES

Stability Condition to Avoid:SPRAYING NEAR FLAME OR HOT SURFACES Hazardous Decomposition Products:WHEN INV

OLVED IN F	IRE, PRODUCT EMI ⁻	TS		
TOXIC AN	ID IRRITATING FUM	ES OF HYDROGEN	I CHLORIDE, HYDF	ROGEN FLUORIDE 8
CARBON	/L HALIDE			

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL REGULATIONS. DO NOT PUNCTURE OR INCINERATE AEROSOL CANS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Ame rica in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.