View NSN Online: https://aerobasegroup.gr/nsn/6750-00-032-0622

EASTMAN KODAK COMPANY -- 155 8949, METAL ETCH RESIST DEVELOPER -- 6750-00-032-0622

Product ID:155 8949, METAL ETCH RESIST DEVELOPER

MSDS Date:01/01/1985

FSC:6750

NIIN:00-032-0622

MSDS Number: BCVSS === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-722-5151

Emergency

Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

====== Composition/Information on Ingredients ========

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000 Fraction by Wt: 45.0%

OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 55.0% OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293
======================================
Effects of Overexposure:SKIN:REPTD/PROLNGD LIQ CONTCT CAUSES DEFATTNG;EYES:CONTACTW/LIQUID CAUSES IRRITATION*SEE SUPP DATA*
======================================
First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED ATTN;EYES:FL
USH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN.FOR IRRIT GET MED ATTN.
======================================
Flash Point:86F(30C)-TCC Lower Limits:0.8% Upper Limits:7.0% Extinguishing Media:CO*2,DRY CHEM,DRY FOAM Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT W/WATER SPRAY. Unusual Fire/Explosion Hazard:SPILL/RUNOFF MAY CAUSE POLUTION,FIRE/EXPLOSION HAZARD;CONTNRS(EMPTY/FULL)MAY EXPLODE IN HEAT OF FIRE
========= Accidental Release Measures ==========
Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN SOURCES.USE PROTCTV/SAFETY EQUIP.STOP LEAK W/O RISK.PROVIDE VENT.DIKE LG SPILL.PUMP LIQ TOSALVAGE TANK.ABSORB REMAINING LIQ W/ABSRBNG MATL & SHOVEL INTO DRUMS;PER MFR SOAK UP SM SPILL W/ABSRBNT MATL IAWREGS.
============ Handling and Storage ===============
Handling and Storage Precautions:STORE AWAY

DOT Rpt Qty:1000 LBS

FROM SOURCE OF IGN.STORE IN COOL, DRY, PLACE. KEEP CONTNRS TIGHTLY CLOSED. PROTECT CONTNRS FROM PHYSICALDAMAGE.
Other Precautions: AVOID SKIN/EYE CONTACT W/CHEMICAL PRODUCTS. WASH THOROUGHLY AFTER HANDLING USING PLENTY OF WATER.
====== Exposure Controls/Personal Protection =======
Respiratory Protection:AN APPRVD ORGANIC VAP RESPIRATOR FOR EMERGENCY USE ONLY
Ventilation:LOCAL EXHAUST & MECHANICAL(GENERAL) RECOMMENDED BY MFGR. Protective Gloves:IMPERVIOUS Eye Protection
:SAFTEY GLASSES/GOGGLES Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.
Supplemental Safety and Health *INHALATION EFFECT:PROLONGED EXPOSURE TO HIGH VAP CONC MAY CAUSE ANESTHETIC EFFICT ALONG WITH HEADACHE, DIZZ & NAUSEA; MSDS FM MFR DTD:12/15/77
========= Physical/Chemical Properties ==========
HCC:F4 Boiling Pt:B.P. Text:291-360F Vapor Density:4 Spec Gravity:0.8121 Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS LIQ+ PETROLEUM ODOR Perce nt Volatiles by Volume:100
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES OXIDIZING & CORROSIVE MATERIAL Stability Condition to Avoid:SOURCE OF INGNITION Hazardous Decomposition Products:BURNING MAY RESULT IN EVOLUTION OF CO & CO*2.
======== Disposal Considerations ===========

Waste Disposal Methods:KEEP IN COVERED CONTNRS PENDING DISPOSAL.SHIP WASTE MATL IAW DOT TO DISPOSAL/INCINERATING FACILITY.H

ANDLE/DISPOSE

IN FULL COMPLIANCE W/ALL FED ,STATE,LOCAL REGS;MFR RECOMMENDS:BURN-TREAT AS ORGANICSOL VNTS.FED,ST.& LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.