View NSN Online: https://aerobasegroup.com/nsn/8040-00-097-6524

Product ID:DAPCOTAC # 3300 COMP."B" MSDS Date:01/01/1987 FSC:8040 NIIN:00-097-6524 Kit Part:Y **MSDS Number: BCYNN** === Responsible Party === Company Name: D AIRCRAFT PRODUCTS CO. Address:1191 HAWK CIRCLE City:ANAHEIM State:CA ZIP:92807 Info Phone Num:714-632-8444 Emergency Phone Num:714-632-844 4 CAGE:58093 === Contractor Identification === Company Name: D AIRCRAFT PRODUCTS CO Address:1191 HAWK CIR Box:City:ANAHEIM State:CA ZIP:92708 Country:US Phone:714-632-8444 CAGE:58093

Ingred Name:ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 40% OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 50% OSHA PEL:200 P PM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INGESTION: MILDLY TOXIC. MAY CAUSE VOMITING, STOMACH CRAMPS, NAUSEA. SKIN: MAY CAUSE IRRITATION OR DRYNESS. INHALATION: MILD IRRITATION OF NOSE, THROAT, MAY CAUSE HEADACHE. EYES: MODERATELY IRRITATI

NG TO EYES.

Effects of Overexposure: IRRITATION TO EYE, SKIN AND RESPIRATORY TRACT. Medical Cond Aggravated by Exposure: SKIN AND RESPIRATORY DISORDERS.

First Aid:INGESTION: GET MEDICAL ATTENTION, PROMPTLY. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION AND GET MEDICAL ATTENTION AS SOON AS POSSIBLE. EYES: FLUSH EYES IMMEDIATELY WITH LARGE QUANTITIES OF WATER, GET MEDICAL ATTENTION.

Flash Point Method:COC Flash Point:35F,1.6C Lower Limits:1.3 Upper Limits:12.7 Extinguishing Media:WATERSPRAY, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL OR UNIVERSAL TYPE FOAMS Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:FLAMMABLE MATERIAL

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. USE ABSORBENT MATERIAL TO ABSORB THE SPILL. USE PROPER VENTILATION. Neutralizing Agent:NONE

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS AND FLAME. STORE AT COOL TEMPERATURES BELOW 75 DEG F, IN CLOSED CONTAINERS. Other Precautions: WHEN APPLYING, USE ENOUGH VENTILATION.

======= Exposure Controls/Personal Protection ==========

Resp

iratory Protection:NONE REQUIRED IN NORMAL USE.
Ventilation:MECHANICAL (GENERAL) RECOMMENDED.
Protective Gloves:RUBBER GLOVES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYE BATH, SAFETY SHOWER.
Work Hygienic Practices:WASH THOROUGHLY AFTER USE. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
PART B OF A 2 PART PRODUCT. SEE P/N IND A, THIS NSN, FOR ADDITIONAL INFORMATION.

HCC:F2

Boiling Pt:B.P. Text:200F,93C Vapor Pres:28.3 Vapor Density:>1 Spec Gravity:0.85 Evaporation Rate & amp; Reference:>1 (BUTYL ACETATE=1) Solubility in Water:REACTS Appearance and Odor:CLEAR COLORLESS LIQUID WITH MILD SOLVENT ODOR Percent Volatiles by Volume:>50

Stability Indicator/Materials to Avoid:YES WATER AND OXIDIZING AGENTS Stability Condition to Avoid:KEEP AWAY FROM HEAT, SPARKS OR ANY SOURCE OF IGNITION. Hazardous D ecomposition Products:CO, CO2, OXIDES OF NITROGEN AND SILICONE

Waste Disposal Methods:DISPOSE ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate an d disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.