GOODYEAR AEROSPACE CORP/AKRON, OH 44315-0001 -- INSULATOR, 1630-00-106-6794 ============= Product Identification ======================== Product ID: INSULATOR, #9536207 MSDS Date:01/01/1987 FSC:1630 NIIN:00-106-6794 MSDS Number: BCYWM === Responsible Party === Company Name: GOODYEAR AEROSPACE CORP/AKRON, OH 44315-0001 Emergency Phone Num:(216) 796-2121 CAGE:EO533 === Contractor Identification === Company Name: GOODYEAR AEROSPACE CORPORATION Address:1210 MASSILLON ROAD City:AKR ON State:OH ZIP:44315 Phone: (216) 796-2121 CAGE:EO533 Company Name: LORAL CORP DEFENSE SYSTEMS DIV-AKRON Address:1210 MASSILLON RD Box:City:AKRON State:OH ZIP:44315-0001 Country:US Phone:216-796-2800 CAGE:25500 ======= Composition/Information on Ingredients ========

#9536207

Ingred Name: ASBESTOS (CHRYSOTILE) 65-70%

RTECS #:GC2625000 Fraction by Wt: 70% ACGIH TLV:2.0 FB/CC

Ingred Name:PHENOL-FORMALDEHYDE RESIN 26-35%

Fraction by Wt: 35%

===== Hazards Identification ======

Effects of Overexposure:CHRONIC OVEREXPOSURE TO AIRBORNE CONCENTRATIONS OF ASBESTOS MAY LEAD TO ASBESTOSIS & MESOTHELIOMA
======================================
First Aid:INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE. SKIN: WASH WITH SOAP & WATER. EYE: FLOOD WITH WATER. IF IRRITATION OCCURS, SEE A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN. CHANGE CLOTHING, IF NECESSARY/AVOID DUSTS PARTICLES IN OTHER AREAS
====== Fire Fighting Measures ====================================
Flash Point:NONE Fire Fighting Procedures:COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE SCBA.
========= Accidental Release Measures ===========
Spill Release Procedures:VACUUM OR WET CLEAN IF DUST IS INVOLVED. VACUUM SYSTEM SHOULD BE EQUIPPED WITH AN OUET HEPA FILTER TO PREVENT REINTRODUCING ASBESTOS FIBERS TO THE ATMOSPHER
======================================
Handling and Storage Precautions:HANDLE TO MINIMIZE FORMATION OR RETENTION OF DUST.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF >TLV, A NIOSH/MSHA APPROVED RESPIRATOR FOR ASBESTOS.  Ventilation:LOCAL EXHAUST VENTILATION IS RECOMMENDED Eye Protection:SAFETY GOGGLES/FACE SHIEL Supplemental Safety and Health MSDS DATE: 4/85
========== Physical/Chemical Properties ==========
HCC:T7 Boiling Pt:B.P. Text:NONE

Solubility in Water:0

========= Stability and Reactivity Data ==========	
Stability Indicator/Materials to Avoid:YES	
======= Disposal Considerations ==========	

Appearance and Odor: DARK BROWN SOLID

Percent Volatiles by Volume:0

Waste Disposal Methods:DUST SHOULD BE HANDLED AS HAZARDOUS AIR POLLUTANT IN ACCORDANCE W/40 CFR 61 SUBPART M PERTAINING TO ASBESTOS. USE LANDFILLS FOR ASBESTOS DISPOSAL. SCRAP PARTS ARE NOT FRIABLE AND ARE NOT RESTRICTED UN DER AIR POLLUT ION REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.