View NSN Online: https://aerobasegroup.gr/nsn/8010-00-165-4432

Product ID:VARNISH, SPAR TT-V-121 MSDS Date:01/01/1985 FSC:8010 NIIN:00-165-4432 **MSDS Number: BDDTS** === Responsible Party === Company Name: CORONADO PAINT COMPANY, INC. Emergency Phone Num:904 428-6461 CAGE:33200 === Contractor Identification === Company Name: CORONADO PAINT COMPANY, INC. Ad dress:308 OLD COUNTY ROAD Box:City:EDGEWATER State:FL ZIP:32132-1812 Country:US Phone:904-428-6461 CAGE:33200

Ingred Name:AROMATIC & ALIPHATIC HYDROCARBON RTECS #:ZE2190000 Fraction by Wt: 44.7% ACGIH TLV:200 PPM

Ingred Name:POLYURETHANE & ALKYD RESIN Fraction by Wt: 55.3% ACGIH TLV:NO HAZARD

Effects of Overexposure: PRODUCES SEVERE EYE IRRITATION, DRYING OF SKIN. EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS.

First Aid:EYES CONTACT-FLUSH WITH WATER. SKIN CONTACT-WASH WITH MILD SOAP AND WATER AND APPLY SKIN CREAM. INHALATION-REMOVE TO FRESH AIR AND CALL A PHYSICIAN, APPLY ARTIFICAL RESPIRATION IF NECESSARY.

Flash Point:92F SETA Lower Limits:1.0 Upper Limits:7.0 Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:TREAT AS CLASS B FIRE. Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPOSUREO SPARKS, FIRE, OR HOT METAL SURFACES.

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR PEATED CONTACT WITH SKIN.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:SELF CONTAINED NIOSH APPROVED PROTECTION IF TLV IS EXCEEDED. Ventilation:LOCAL EXHAUST Protective Gloves:YES Eye Protection:YES Other Protective Equipment:EYE BATH AND SAFETY SHOWER. Supplemental Safety and Health 308 OLD COUNTY ROAD, EDGEWATER, FLORIDA 32032

======= Physical/Chemic

HCC:F3 Boiling Pt:B.P. Text:280 Vapor Pres:6 Vapor Density:3.7 Spec Gravity:0.92 Evaporation Rate & amp; Reference:0.6 Solubility in Water:VERY SLIGHT Appearance and Odor:CLEAR LIQUID, PETROLEUM DISTILLATE ODOR. Percent Volatiles by Volume:52.9

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES OR FIRE. Hazardous Decomposi

tion Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE.

Waste Disposal Methods:LAND FILL, INCINERATION UNDER SAFE AND SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.