View NSN Online: https://aerobasegroup.com/nsn/4210-00-165-4703

R.C.INDUSTRIES,INC. -- ABC DRY CHEMICAL POWDER -- 4210-00-165-4703

Product ID:ABC DRY CHEMICAL POWDER

MSDS Date:01/01/1985

FSC:4210

NIIN:00-165-4703

MSDS Number: BDDTW === Responsible Party ===

Company Name: R.C. INDUSTRIES, INC.

Box:2620

City:NEW BRUNSWICK

State:NJ ZIP:08903 Country:US

Emergency Phone Num: NONE

CAGE:KO385

=== Contractor Identification ===

Company N

ame:R.C.INDUSTRIES,INC.

Box:2620

City:NEW BRUNSWICK

State:NJ ZIP:08903 Country:US CAGE:KO385

Company Name: USE CAGE CODE 60002 PLEASE (THIS WAS REPLACED).

Box:2620

City:NEW BRUNSWICK

State:NJ ZIP:08903 Country:US

Phone:201-937-5400

CAGE:2F721

======= Composition/Information on Ingredients ========

Ingred Name: DYE-YELLOW

Fraction by Wt: 0.03%

Ingred Name: SILACEOUS MATERIAL

Fraction by Wt: 4.5% ACGIH TLV:20 MPPCF

Ingred Name: MONOAMMONIUM DIHYDROGEN PHOSPHATE

Fraction by Wt: 95.0%

Ingred Name:MIXTURE OF NITROGEN & FREON GAS Fraction by Wt: 0.47%
=========== Hazards Identification ============
Effects of Overexposure:IRRITATION TO EYES,SKIN,& NASAL PASSAGES
======================================
First Aid:EYE CONTACT:FLUSH EYES THOROUGHLY WITH WATER.CONSULT DOCTOR.INHALATION & SKIN CONTACT:REMOVE VICTIM FROM EXPOSURE. WASH ALL EXPOSED AREAS WITH SOAP & WATER.IF IRRITATON PERSISTS,CONSULT DOCTOR
======== Fire Fighting Measures ====================================
Flash Point:N.A. Extinguishing Media:THIS MATERIAL IS A FIRE EXTINGUISHING AGENT Fire Fighting Procedures:N.A. Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ==========
Spill Release Procedures:PROMPTLY SWEEP,WIPE CLEAN,BLOW AWAY FROM AIRLINES,OR WHERE POSSIBLE,WASH WITH WATER
=========== Handling and Storage ============
Handling and Storage Precautions:STORE MAT ERIAL IN A COOL,DRY PLACE.DO NOT EXPOSE MATERIAL TO HIGH HUMIDITY CONDITIONS.
===== Exposure Controls/Personal Protection =======
Respiratory Protection:USE DUST MASK TO ELIMINATE DUST INHALATION Ventilation:AS REQUIRED TO CONTROL DUST Supplemental Safety and Health THE ITEM IS SIZE 5 IN FEDERAL SPEC. O-E-915 TYPE I CLASS I. PER SPEC A-A-393A, A PROPELLANT WILL BE USED TO EXPEL THE EXTINGUISHING AGENT (DRY CHEMICALS).
======== Physical/Chemical Properti

HCC:G3 Boiling Pt:B.P. Text:N.A. Spec Gravity:1.8 Evaporation Rate & Description of the Company
======== Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES

Waste Disposal Methods:PUT IN APPROVED STORAGE CONTAINER & SHIP TO APPROVED DISPOS AL AREA.

======= Disposal Considerations ===========

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particul

ar situation.