## 

City:STAMFORD

State:CT ZIP:06907 Country:US

ı

nfo Phone Num:203-353-0300

Emergency Phone Num:203-353-0300

CAGE:0CSD2

=== Contractor Identification ===

Company Name: FUJI MEDICAL SYSTEMS INC FUJI NDT SYSTEMS DIV

Address:90 VIADUCT RD

City:STAMFORD

State:CT ZIP:06907 Country:US

Phone:203-353-0300

CAGE:0CSD2

======= Composition/Information on Ingredients ========

Ingred Name: HYDROQUINONE (SARA III)

CAS:123-31-9

RTECS #:MX3500000 Fraction by Wt: 4-8% OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingr

ed Name:SODIUM SULFITE CAS:7757-83-7 RTECS #:WE2150000 Fraction by Wt: 10-30% ACGIH TLV:UNK Ingred Name: SODIUM TETRABORATE, DECAHYDRATE CAS:1303-96-4 RTECS #:VZ2275000 Fraction by Wt: 1-4% OSHA PEL:10 MG/M3 ACGIH TLV:5 MG/M3; 9192 Ingred Name: POTASSIUM HYDROXIDE (SARA III) CAS:1310-58-3 RTECS #:TT2100000 Fraction by Wt: 2-6% OSHA PEL:C, 2 MG/M3 ACGIH TLV:C 2 MG/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name:SODIUM BROMIDE CAS:7647-15-6 RTECS #:VZ3150000 Fraction by Wt: 1-3% **CGIH TLV:UNK** ========== Hazards Identification =============== Routes of Entry: Inhalation: NO Skin: YES Ingestion: YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SEE OVEREXPOSURE. OF SKIN IRRITATION OR DERMATITIS.

Effects of Overexposure:BURNING OF EYES & MUCOUS MEMBRANES;DEVELOPMENT

Medical Cond Aggravated by Exposure: NONE KNOWN.

First Aid:EYES-FLUSH W/WATER

15 MIN;GET MED ATTN. SKIN-FLUSH WELL W/WATER;IF IRRIT DEVELOPS,GET MED ATTN. INGEST-GET IMMED MED ADVICE GIVING DETAILS ON QTY SWALLOWED & TOXICITY.
======================================
Extinguishing Media:AS APPROPRIATE TO EXTINGUISH SOURCE OF FIRE. Fire Fighting Procedures:NONE. Unusual Fire/Explosion Hazard:NONE.
========= Accidental Release Measures ==========
Spill Release Procedures:WEAR PROTECT CLOTH. IF FED,STATE OR LOCAL REG
PERMIT, NEUTRALIZE W/SODIUM BISULFATE & FLUSH TO SEWER W/LGE AMTS WATER. OTHERWISE, ADD DRY ABSORBENT, CLEAN UP & PLACE IN APPROVED DOT CONTNR, LABEL, & SEAL FOR DISPOSAL.  Neutralizing Agent: SODIUM BISULFATE.
============ Handling and Storage ============
Handling and Storage Precautions:KEEP TIGHTLY SEALED. DO NOT STORE OR CONSUME FOOD,DRINK OR TOBACCO IN AREA WHERE THEY COULD BE CONTAMINATED W/MATL. STORE ABOVE 40F/4C.  Other Precautions:AVOID UNNECESSAR Y PERSONAL CONTACT. AVOID INCOMPATIBLE SUBSTANCES. WASH THOROUGHLY AFTER HANDLING. ROUTINE USE OF NON-ALKALINE HAND CLEANER WILL MINIMIZE POSSIBLITY OF ALLERGIC SKIN REACTION.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE SHOULD BE NEEDED.  Ventilation:GOOD GENERAL VENTILATION.  Protective Gloves:IMPERVIOUS.  Eye Protection:SAFETY GLASSES/GOGGLES.  Other Protective Equipment:AS NECESSARY TO PREVENT SKIN OR EYE CONTACT.  Supplemental Safe ty and Health  KEY1:B3. THIS IS PART A OF A 3-PART KIT. SEE PNI B & C.
======== Physical/Chemical Properties =========
HCC:F6 Boiling Pt:>100.C, 212.F Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.29 pH:11.2 Solubility in Water:COMPLETE Appearance and Odor:SLIGHTLY YELLOWISH ODORLESS LIQUID. Percent Volatiles by Volume:80 Corrosion Rate:NONE
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES MINERAL ACIDS.

Stab

ility Condition to Avoid:NONE KNOWN.
Hazardous Decomposition Products:SULFUR DIOXIDE

======= Disposal Considerations ===========

Waste Disposal Methods: CONSULT PROPER FED, STATE & LOCAL REGULATORY AGENCIES FOR PROPER PROCEDURES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrant

s this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.