

3M GENERAL OFFICES -- SCOTCH-SEAL(TM)BRAND IND SEALANT 801 -- 8030-00-174-3199
===== Product Identification =====

Product ID:SCOTCH-SEAL(TM)BRAND IND SEALANT 801

MSDS Date:06/30/1987

FSC:8030

NIIN:00-174-3199

MSDS Number: BDFNS

=== Responsible Party ===

Company Name:3M GENERAL OFFICES

Address:3M CENTER

City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone N

um:612-733-1110

CAGE:04963

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

===== Composition/Information on Ingredients =====

Ingred Name:POLYSULFIDE RUBBER

Fraction by Wt:

Other REC Limits:

OSHA PEL:

ACGIH TLV:

Ingred Name:PHENOLIC RESIN

Fraction by Wt:

Other REC Limits:

OSHA PEL:

ACGIH TLV:

Ingred

Name:SILICA, AMORPHOUS, DUST
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt:
Other REC Limits:20 MPPCF
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3; 8990

Ingred Name:CARBON BLACK
CAS:333-86-4
RTECS #:FF5800001
Fraction by Wt:
Other REC Limits:3.5 MG/CUM
OSHA PEL:3.5 MG/CUM
ACGIH TLV:3.5 MG/CUM

Ingred Name:MAGNESIUM ACETATE
CAS:142-72-3
RTECS #:AI5600000
Fraction by Wt:
Other REC Limits:
OSHA PEL:
ACGIH TLV:

Ingred Name:PETROLEUM DISTILLATE
Fraction by Wt: 3.0%
Other REC Limits:
OSHA PEL:
ACGIH TL
V:

===== Hazards Identification =====

Effects of Overexposure:EYE:IRRITATION. SKIN: IRRITATION CONTACT W/
SKIN WILL CAUSE EXTREME DIFFICULTY IN CLEAN UP. USE OF ABRASIVES OR
SOLVENTS FOR CLEANUP COULD CAUSE SKIN DAMAGE. INHAL:NO HAZARD.VAPOR
OVEREXPOSURE:RESP IR RITATION LIGHT-HEADEDNESS. SYMPTOMS
HEADACHE,WEAKNESS,FATIGUE OR UNCONSCIOUSNESS. INGEST, DIGESTIVE
SYSTEM IRRITATION.

===== First Aid Measures =====

=====

First Aid:EYE: FLUSH W/ LG AMTS OF H*2O FOR AT LEAST 15 MIN CALL PHYS.
SKIN:WASH THOROUGHLY W/ SOAP + H*2O INHAL:REMOVE INDIVIDUAL TO
FRESH AIR. CALL PHYSICIAN.INGEST:DO NOT INDUCE VOMITING.DRINK TWO
GLASSES OF MILK OR H*2O.CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:7100F-37.78C
Extinguishing Media:CO2,FOAM,DRY CHEM.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD BE EQUIPPED W/ SCBA.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL.CLEAN UP RESIDUE + AREA OF
SPILL.PLACE RESIDUE IN CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS AND OPEN
FLAME. USE ONLY WITH ADEQUATE VENTILATION TO REMOVE AND PREVENT
VAPOR BUILD UP. KEEP CONTAINER CLOSED.
Other Precautions:AVOID PROLONG BREATHING OF VAPORS AND PROLONGED OR
REPEATED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN
Ventilation:USE ONLY IN AREAS W/ ENOUGH AIR MOVEMENT TO PREVENT VAPOR
BUILD UP.
Protective Gloves:IMPERVIOUS
Eye Protection:CHEM GOGGLES
Supplemental Safety and Health
PART A OF A TWO PART KIT.KEY1:J1.

===== Physical/Chemical Properties =====

HCC:F4
Spec Gravity:1.36
Solubility in Water:LOW
Appearance and Odor:BLACK

SULFUR ODOR

Percent Volatiles by Volume:3

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO2,SULFUR COMPOUND

===== Disposal Considerations =====

Waste Disposal Methods:MAY BE DISPOSED OF IN A SANITARY LANDFILL
ACCORDING TO LOCAL + CURRENT U.S.ENVIRONMENTAL PROTECTION AGENCY
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.