View NSN Online: https://aerobasegroup.gr/nsn/6850-00-177-8021
BENSON INC BENSON PREMIX TONER 6850-00-177-8021 ====================================
Product ID:BENSON PREMIX TONER MSDS Date:01/01/1987 FSC:6850 NIIN:00-177-8021 MSDS Number: BDFVS === Responsible Party === Company Name:BENSON INC. Emergency Phone Num:415 966 9561 CAGE:4X257 === Contractor Identification === Company Name:BENSON INC. CAGE:4X257
======= Composition/Information on Ingre dients =========
Ingred Name:MIXED ISODECANES Fraction by Wt: >99%. ACGIH TLV:300PPM
Ingred Name:CARBON BLACK TREATED WITH AN INSOLUBLE RESINOUS MIXTURE. Fraction by Wt: 0.5%
============ Hazards Identification =============
Effects of Overexposure:INHAL:NAUSEA,HEADACHE;FOR MORE SEVERE EXP.MILD DEPRESS.&/OR RESP.IRRITINGEST:UPSET STOMACH.,IRRIT.
======================================
First Aid:INHAL:REMOVE TO FRESH AREAINGEST:DO NOT INDUCE VOMIT;CALL DOCTOR IMMEDIATELYEYES:FLUSH WITH WATER FOR 15 MIN.IF IRRIT.PERSISTS,CALL DOCTOR.
======================================
Flash Point:104.5F,40C,TCC Lower Limits:0.8 Upper Limits:7.0 Extinguishing Media:FOAM-TYPE EXTINGUISHERS-SUPERIOR TO CO*2 EXTINGUISHERS. Fire Fighting Procedures:AVOID WTR;IT TENDS TO SPREAD HYDROCARBONS SOLVENT FIRES.
========= Accidental Release Measures ==========
Spill Release Pro

cedures:REMOVE IGN.SOURCES.IF AMT.IS SMALL(LESS THAN 1 PINT),ALLOW TO EVAPIF AMT IS LARGE,TRY TO CONTAIN & SOP UP AS MUCH AS POSSIBLE INTO A CNTNR THAT CAN BE CLOSED.
======================================
Handling and Storage Precautions:KEEP CNTNRS CLOSED.AVOID STORAGE NEAR HEAT,STRG LIGHT (IF CNTNRS ARE CLEAR),SPARKS,OR OPEN FLAME. Other Precautions:AVOID USE IN A SMALL CLOSED ROOM OR IN A CONFINED AREA WITH POOR AIR CIRCULATIONS.
======================================
Respiratory Protection:NONE Ventilation:NORMAL AIR CONDITIONING IS ADEQUATE. Protective Gloves:NONE Eye Protection:NONE Other Protective Equipment:NONE Supplemental Safety and Health UNDATED MSDS.
======================================
HCC:F4 Boiling Pt:=166.7C, 332.F Vapor Pres:99.
========== Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES STRG OXIDANTS LIKE CHROMIC AC.,LIQ.CHLORINE,CONC.OXYGEN. Hazardous Decomposition Products:INCOMPLETELY BURNED CARBON PRODUCTS, CO*2, CO.
========= Disposal Considerations =============
Waste Disposal Methods:LG.CNTNRS OF WASTE MUST BE HANDLED BY PERSONS OR FIRMS WITH FACILITIES FOR DISPOSAL,E.G.,CONTROLLED BURNING.
Disclaimer (provided with this information by the compiling agencies):

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United

States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.