

AMERON-INDUSTRIAL COATINGS DIVISION -- 742-618,TT-E-489F,COMP L,CLASS A,GRAY --
8010-00-200-8810

===== Product Identification =====

Product ID:742-618,TT-E-489F,COMP L,CLASS A,GRAY

MSDS Date:01/01/1987

FSC:8010

NIIN:00-200-8810

MSDS Number: BDJGW

=== Responsible Party ===

Company Name:AMERON-INDUSTRIAL COATINGS DIVISION

Box:B

City:PARKERSBURG

State:WV

ZIP:26101

Country:US

CAGE:KO581

=== Contracto

r Identification ===

Company Name:AMERON-INDUSTRIAL COATINGS DIVISION

Box:B

City:PARKERSBURG

State:WV

ZIP:26101

Country:US

CAGE:KO581

Company Name:UNION INSULATING CO

Box:B

City:PARKERSBURG

State:WV

ZIP:26101

Country:US

CAGE:83090

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:INH:

ANESTHETIC,RESP TRACT IRRIT OR CNS
DEPRESS(HDACHE,DIZZ,UNCONSCNS) EYE/SKIN CONTCT:IRRIT.

===== First Aid Measures =====

First Aid:IN CASE OF CONTCT,FLUSH SKIN & EYES W/PLENTY OF WATER WHILE
REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH AIR.CALL
A PHYSICIAN IF SYMPTOMS PERSIST.

===== Fire Fighting Measures =====

Flash Point:85 F (TCC)

Lower Limits:1.10

Extinguishing Media:CO*2,DRY CHEMICAL OR ALCOH
OL FOAM.LRGE FIRE-POLYMER
FOAM.

Fire Fighting Procedures:SCBA.H*2O SPRAY-NOT RECM. H*2O (FOG NOZZ)-COOL
CLSD CONTR

Unusual Fire/Explosion Hazard:KEEP CONTR TIGHTLY CLSD.ISOLATE FROM IGN
SOURCES.CLSD CONTR-POSS EXPLO IF EXPOSED TO EXTREME HEAT

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.AVOID BREATHING
VAPORS.VENTILATE AREA.REMOVE W/INERT ABSORBENT & NON-SPARKING
TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE
QUANTITIES IN BUILDING DESIGNED TO COMPLY W/OSHA 1910.106.

Other Precautions:GROUND CONTAINER WHEN POURING.AVOID LIQUID FREE FALL
IN EXCESS OF A FEW INCHES.FLAME CUT,BRAZE OR WELD COATED
MATERIAL-USE NIOSH/MSHA APPRVD RESP EQUIP OR PROPER VENTILN.ADD
LABEL WARNING

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOOR/OPEN,

RESTRICTED OR CONFINED

AREAS-NIOSH/MSHA APPRVD EQUIP.

Ventilation:GENRL DILUTION/LOCAL EXHAUST TO KEEP TLV BELOW STATED
LIMIT.

Protective Gloves:REQUIRED

Eye Protection:REQUIRED

Supplemental Safety and Health

EMERGENCY TELEPHONE NO. (NIGHT)-(800) 424-9300.DO NOT APPLY TO HOT
SURFACES.PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.DO
NOT TAKE INTERNALLY.CONTAINER SIZE:5 GAL

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:

311-373 F

Vapor Pres:3.2

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER.

Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL,STATE & FEDERAL
REGULATONS.MFR RECM- INCINERATE IN A APPRVD FACILITY.DO NOT

INCINERATE IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this inform

ation to their
particular situation.