

PRATT & LAMBERT-WICHITA DIVISION -- 742-618 -- 8010-00-200-8810

=====  
Product Identification  
=====

Product ID:742-618

MSDS Date:01/01/1985

FSC:8010

NIIN:00-200-8810

MSDS Number: BDJGX

=== Responsible Party ===

Company Name:PRATT & LAMBERT-WICHITA DIVISION

Emergency Phone Num:316-733-1361

CAGE:KO010

=== Contractor Identification ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Box:2153

CAGE:KO010

Com

pany Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 50.0%

OSHA PEL:100 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALED:ANESTHETIC & IRRITATION TO AIR WAYS;  
IRRITATION-SKIN/EYE CONTACT;HEADACHE,DIZZY,

COMA

=====  
===== First Aid Measures =====

First Aid:FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING  
CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH AIR.CALL A DOCTOR  
IF SYMPTONS PERSIST.

=====  
===== Fire Fighting Measures =====

Flash Point:104 F, 40 C, TCC

Lower Limits:1.1

Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL;POLYMER  
FOAM-LARGE FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVA  
ILABLE  
FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE DUE TO PRESURE BUILD-UP,USE H\*2O TO COOL CLOSED CANS

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT  
SURFACES, & ELECTRICAL,STATIC OR FRICTIONAL SPARKS).AVOID BREATHING  
VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING  
TOOLS

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE  
AMTS.IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS  
ONE FLAMMABLE (OR COMBUSTIBLE)LIQUID

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED  
WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME  
CUT,BRAZE OR WELD COATED MATERIAL WITHOUT VENTILATION.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED

BUREAU OF MINES RESPIRATORS W/PROPER  
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY& WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING.

Supplemental Safety and Health

BOILING RANGE 155-189 C

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373 F

Evaporation Rate & Reference:< ETHER

Appearance

Color and Odor:GRAY PAINT

Percent Volatiles by Volume:61.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRES,HEAT, & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND  
FEDERAL REGULATIONS.INCINERATE IN APPROVED FACILITY.DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.