

SPE-DE-WAY PRODUCTS CO.,INC. -- THINNER PAINT; TT-T-291, TYPE 1, GRADE A --  
8010-00-246-6116

=====  
Product Identification  
=====

Product ID:THINNER PAINT; TT-T-291, TYPE 1, GRADE A

MSDS Date:01/01/1987

FSC:8010

NIIN:00-246-6116

MSDS Number: BDNJB

=== Responsible Party ===

Company Name:SPE-DE-WAY PRODUCTS CO.,INC.

CAGE:33439

=== Contractor Identification ===

Company Name:SPE-DE-WAY PRODUCTS CO INC

A

Address:8000 N E 14TH PLACE

Box:17192

City:PORTLAND

State:OR

ZIP:97217

Country:US

CAGE:33439

Company Name:WOOD-KOTE PRODUCTS INC FRMLY SP-DE-WAY PROD.

Address:8000 N.E. 14TH PLACE

Box:City:PORTLAND

State:OR

ZIP:97217

Country:US

Phone:1-800-535-5053

CAGE:33429

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PARAFFINS (INCLUDING NAPHTHENES)

Fraction by Wt: 92.0%

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 1.0%

OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:AROMATIC COMPOUNDS CONTAINING MORE THAN EIGHT CARBONS.  
Fraction by Wt: 7.0%

=====  
Hazards Identification  
=====

Effects of Overexposure:MAY CAUSE EYE IRRITATION, SKIN DERMATITIS.  
INHAL MAY SHOW SIGNS OF CNS DEPRESSION.

=====  
First Aid Measures  
=====

First Aid:FLUSH EYES AT LEAST 15 MIN. INHAL: REMOVE TO FRE  
SH AIR.  
INGEST: DO NOT INDUCE VOMITING. CONSULT MD.

=====  
Fire Fighting Measures  
=====

Flash Point:100F TCC  
Lower Limits:1.0  
Upper Limits:6.0  
Extinguishing Media:CO\*2, DRY CHEMICAL, FOAM, WATER SPRAY  
Fire Fighting Procedures:USE SELF-CONTANED OBA IN ENCLOSED SPACE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION IN VICINITY OF  
SPILL OR RELEASED VAPORS. CLEAN UP AS SOON AS POSS  
IBLE.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT OR OPEN FLAME.  
AVOID PROLONGED OR REPEATED BREATHING OF VAPOR OR SKIN & EYE  
CONTACT.  
Other Precautions:HARMFUL OR FATAL IF SWALLOWED

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IN HIGH CONC USE APPROVED RESPIRATOR OR  
SELF-CONTAINED OBA  
Ventilation:ADEQUATE TO KEEP VAPOR OR MIST BELOW SUGGESTED TLV  
Protective

Gloves:RUBBER

Eye Protection:CHEMICAL GOGGLES

Supplemental Safety and Health

VAPOR PRESSURE IS GIVEN AT 77.8F CONFORMS TO TT-T-291, TYPE 1, GRADE A

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:313-404 F

Vapor Pres:5.0

Vapor Density:4.9

Spec Gravity:0.801

Evaporation Rate & Reference:0.13 BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS LIQUID

Percent Volatiles by Volume:99.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MAY REACT W/STRONG OXIDIZING MATERIALS

Hazardous Decomposition Products:INCOMPLETE COMBUSTION: CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:ABSORB LARGE SPILLS W/ABSORBENT CLAY OR DIATOMACEOUS EARTH. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, FED REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is f

ormulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.