View NSN Online: https://aerobasegroup.gr/nsn/5970-00-251-8766

DOW CORNING CORPORATION -- DOW CORNING S CATALYST -- 5970-00-251-8766

======== Product Identification ============

Product ID:DOW CORNING S CATALYST

MSDS Date:09/29/1988

FSC:5970

NIIN:00-251-8766

MSDS Number: BDNWR === Responsible Party ===

Company Name: DOW CORNING CORPORATION

Address:3901 S. SAGINAW ROAD

Box:997

City:MIDLAND

State:MI ZIP:48640 Country:US

Info Phone Num:517-496-5900 Emergency Phone Num:517-

496-5900

Preparer's Name: JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name: DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name: DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI ZIP:48611 Country:US

Phone:517-496-4388

CAGE:71984

======= Composition/Information on Ingredients ========

Ingred Name: DIBUTYL TIN DILAURATE (AS TIN)

CAS:77-5

8-7 RTECS #:WH7000000 Fraction by Wt: 5.0% OSHA PEL:S, 0.1 MG/M3 ACGIH TLV:S, 0.1 MG/M3; 8990 Ingred Name: CALCIUM CARBONATE CAS:471-34-1 RTECS #:FF9335000 Fraction by Wt: 16.0% OSHA PEL:10 MG/CUM, AS T DUST ACGIH TLV:10 MG/CUM, AS T DUST ========== Hazards Identification =========================== Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES, SKIN AND RESPIRATORY TRACT, REDNESS OR SWELLING OF EYES, SLIGHT BURNS OF SKIN. CHRONIC: IRRITATION, DERMATITIS. Explanation of Carcinogenicity: NO DATA PER MSDS Effects of Overexposure: IRRITATES SKIN & EYES. Medical Cond Aggravated by Exposure: NO DATA AVAILABLE. First Aid:EYE AND SKIN:FLUSH WITH PLENTY OF WATER FOR ABOUT 15-20 MINUTES:SEEK MEDICAL HELP IF NEEDED. INHALATION:REMOVE TO FRESH AIR. INGESTION: SEEK MEDICAL HELP IMMEDIATELY. Flash Point Method:CC Flash Point:>212F/100C Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM. Fire Fighting Procedures: SELF CONTAINED BREATHING APP./PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard: MAY RELEASE IRRITATING VAPORS DURING

COMBUSTION.

======== Accidental Release Measures ============

Spill Release Procedures: USE ABSORBENT MATERIAL TO COLLECT & CONTAIN FOR DISPOSAL.

==== Handling and Storage ===========
Handling and Storage Precautions:STORE IN COOL & DRY PLACE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE NORMALLY NEEDED IF THERE IS AN ADEQUATE VENTILATION. Ventilation:MECHANICAL(GENERAL) IS RECOMMENDED. Protective Gloves:RUBBER/PLASTIC Eye Protection:SAFETY GLASSES. Other Protective Equipment:APRON,EYE-WASH FACILITIES. Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES;WASH T HOROUGHLY AFTER EACH USE.
Supplemental Safety and Health TLV:0.1MG/CUM BASED ON SN,THE TLV OF SN IS FOR SKIN.
========= Physical/Chemical Properties ==========
HCC:N1 Vapor Pres: