

FILTROL CLAY PRODUCTS,HARSHAW/FILTROL PARTNERSHIP -- FILTROL (CLAY PRODUCTS)
GRADE -- 6850-00-264-6572

=====
Product Identification
=====

Product ID:FILTROL (CLAY PRODUCTS) GRADE

MSDS Date:01/01/1987

FSC:6850

NIIN:00-264-6572

MSDS Number: BDQQC

=== Responsible Party ===

Company Name:FILTROL CLAY PRODUCTS,HARSHAW/FILTROL PARTNERSHIP

Emergency Phone Num:601-948-3966

CAGE:KO962

=== Contractor Identifi

cation ===

Company Name:FILTROL CLAY PRODUCTS,HARSHAW/FILTROL PARTNERSHIP

Address:30100 CHAGRIN BOULEVARD

Box:City:CLEVELAND

State:OH

ZIP:44124-5705

Country:US

Phone:216-292-9200

CAGE:KO962

Company Name:HARSHAW/FILTROL PARTNERSHIP

Address:30100 CHAGRIN BLVD

Box:City:CLEVELAND

State:OH

ZIP:44124-5705

Country:US

Phone:216-349-7300

CAGE:8Z371

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by

Wt: 3.0%
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

===== Hazards Identification =====

Effects of Overexposure:INHAL:LONG-TERM EXPOSURE TO RESPIRABLE XTALINE SILICA MAY CAUSE PNEUMOCONIOSIS;SKINC:CAN DRY SKIN.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR NIOSH APPRVD DUST MASK/RESPIRATOR & RUBBER GLOVES.AVOID CREATING DUST.SWEEP UP OR VACUUM THE AREA. COLLECT DRY MATERIAL IN A DRY,COVERED CONTAINERS.MOIST SURFACES MAY BECOME SLIPPERY.AFTER PICKING WASTE,FLUSH AREA W/LG AMT OF WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED
Other Precautions:AVOID BREATHING DUST.

===== Exposure

Controls/Personal Protection =====

Respiratory Protection:NIOSH OR MSHA APPROVED RESPIRATOR FOR
PARTICULATE

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:RUBBER/NEOPRENE

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

MSDS FM DATED:6/1/1984;ITEM IS TYPE 1 OF MIL-D-3464

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:2.0

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CREAM TO WHITE COLORED POWDER

=====

= Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:WASTE SPILLS COLLECTED MAY BE RECLAIMED/REUSED
OR DISPOSED I/A/W FEDERAL,STATE & LOCAL
REGULATIONS.ALSO,USED/UMUSED PRODUCT SHOULD BE TESTED TO DETERMINE
HAZARD STATUS BEFORE DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.