View NSN Online: https://aerobasegroup.gr/nsn/6810-00-264-9077

Product ID: ETHYL ACETATE MSDS Date:08/18/1986 FSC:6810 NIIN:00-264-9077 MSDS Number: BDRDB === Responsible Party === Company Name: J.T. BAKER CHEMICAL CO Address:222 RED SCHOOL LANE City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Info Phone Num:201-859-2151 Emergency Phone Num:201-859-2151 CAGE:DO870 === Co ntractor Identification === Company Name: J.T. BAKER CHEMICAL CO. Address:222 RED SCHOOL LANE City:PHILLIPSBURG State:NJ ZIP:08865-2219 Country:US Phone:201-859-2151 CAGE:DO870 Company Name: MALLINCKRODT BAKER, INC. Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:800-582-2537 CAGE:70829

Ingred Name:ETHYL ACETATE (SARA III) CAS:141-78-6 RTECS #:AH5425000 Fraction by Wt: 90-100% OSHA PEL:400 PPM ACGIH TLV:400 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:ORA-RAT =11G/KG;LC50:RAT=1600PPM Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Health Hazards Acute and Chronic:ACUTE:IRRITATION OF SIN,EYES AND RESPIRATORY TRACT;DERMATITIS.CHRONIC:KIDNEY AND/OR LIVER DAMAGE. Effects of Overexposure:LIQUID MAY CAUSE DERMATITIS.CHROMIC:MAY INCLUDE KIDNEY AND/OR LIVER DAMAGE.

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES,BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

Flash Point Method:CC Flash Point:24F/-4C Lower Limits:2.2 Upper Limits:11.0 Extinguishing Media:FOAM,DRY CHEMICAL,CO*2 Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA IN CASE OF FIRES. Unusual Fire/Explosion Hazard:VAPORS MAY FLOW ALONG SURFACES TO DISTANT IGNITION SOURCES AND FLASH BACK.CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE.CONTACT WITH STRONG OXIDIZERS MAY C.FIRE

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; USE SUITABLE ABSORBENT MATRIAL AND COLLECT FOR PROPER DISPOSAL.

======================= Handling and Sto

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED AREA BOND & GRUND CONTAINERS WHEN TRANSFERING LIQUID.KEEP CONTAINER TIGHTLY CLOSED

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC MIST/VAPOR IF ABOVE TLV Ventilation: PROVIDE MECHAN (GEN/LOCAL EXHAUST) VENT TO MAINTN TLV Protective Gloves: IMPERVIOUS Eye Protection:SAFETY/CHEM GOGGLES Other Protect ive Equipment: FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT. Work Hygienic Practices: AVOID CONTACT WITH EYES AND SKIN; DO NOT BREATHE VAPORS/OR MIST: WASH THOROUGHLY AFTER EACH USE. Supplemental Safety and Health MSDS WRITTEN IN RESPONSE TO QUESTION FROM A DEPOT FOR TRANSPORTATION INFORMATION. HCC:F2 Boiling Pt:B.P. Text:171F/77C Melt/Freeze Pt:M.P/F.P Text:-119F/-84C Vapor Pres:76MMHG Vapor Density:3. 0 Spec Gravity:0.90 Evaporation Rate & amp; Reference: 6.0 (BUTYL-ACETATE=1) Solubility in Water:MODERATE Appearance and Odor: CLER, COLORLESS LIQUID WITH PLEASANT FRUITY ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS,STRONG ACIDS,STRONG BASES Stability Condition to Avoid:SOURCES OF IGNITION,HEAT,FLAME,HEAT. Hazardous Decomposition Products:DECOMPOSITION MAY GIVE CO OR CO*2 Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use

. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.