

DAVIS-HOWLAND OIL CORP -- MIL-L-83767B;LUBRICATING OIL;TYPE II -- 9150-00-273-8663  
===== Product Identification =====

Product ID:MIL-L-83767B;LUBRICATING OIL;TYPE II

MSDS Date:01/01/1987

FSC:9150

NIIN:00-273-8663

MSDS Number: BDSBL

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORP

Address:200 ANDERSON AVE

City:ROCHESTER

State:NY

ZIP:14607-1111

Country:US

Info Phone Num:716-473-6650

Em

ergency Phone Num:(716) 473-6650

CAGE:FO626

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTE

CS #:PY8030000  
Other REC Limits:5MG/CUM,AS OIL MIST.  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES (TYPE NOT SPECIFIED)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF SKIN OR EYES.  
CHRONIC:NO DATA AVAILABLE.  
Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE  
MILD SKIN IRRITATION;MAY CAUSE EYE IRRITATION.  
Medical Co  
nd Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE  
WORSEN.

===== First Aid Measures =====

First Aid:IN CASE OF SKIN CONTACT,WASH WITH SOAP & WATER;IF SPLASHED  
INTO EYES FLUSH WITH CLEAR WATER UNTIL IRRITATION SUBSIDES.GET MED  
ATTN FOR EYES.

===== Fire Fighting Measures =====

Flash Point:395-475F-(COC)  
Lower Limits:1.0%  
Upper Limits:7.0%  
Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*2O FOG.  
Fire Fighting  
Procedures:USE AIR-SUPPLD RESCUE EQUIP IN CLOSED AREA.  
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.USE PROTCTV  
EQUIPMENTS;RECOVER FREE LIQUID.ADD ABSORBENT TO SPILL AREA.KEEP  
PETROLEUM PRODUCTS OUT OF STREAMS,WATERWAYS & SEWERS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER

S CLOSED;KEEP AWAY FROM

HEAT & OPEN FLAMES;PROTECT CONTAINERS AGAINST PHYSICAL DAMAGE.

Other Precautions:AVOID BREATHING OIL MIST.REMOVE OIL-SOAKED CLOTHING & LAUNDRER BEFORE RE-USE.WASH THOROUGHLY W/SOAP & H\*2O AFTER HANDLING/EXPOSURE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED

Ventilation:LOCAL EXHAUST:TO CAPTURE HOT FUMES & VAPORS.

Protective Gloves:OIL IMPERVIOUS

Eye Protection:AS REQUIRED

Other Protective Equip

ment:USE OIL IMPERVIOUS APRON IF NEEDED.

Supplemental Safety and Health

MFR MSDS NOT DATED;ITEM IS TYPE II OF MIL SPEC MIL-L-83767B,LUBRICATING OIL,VACUUM PUMP,MECHANICAL;SPECIFIC GRAVITY RANGE 0.87-0.90.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:545-900F

Vapor Pres:12

Spec Gravity:0.87-90

Evaporation Rate & Reference: