

ASHLAND CHEMICAL CO. -- TOLUENE -- 6810-00-281-2002

=====
Product Identification
=====

Product ID:TOLUENE
MSDS Date:02/12/1993
FSC:6810
NIIN:00-281-2002
MSDS Number: BDSQB
=== Responsible Party ===
Company Name:ASHLAND CHEMICAL CO.
Box:2219
City:COLUMBUS
State:OH
ZIP:43216
Country:US
Info Phone Num:614-790-3333
Emergency Phone Num:800-274-5263
CAGE:34897
=== Contractor Identification ===
Company
Name:ASHLAND CHEMICAL CO
Box:2219
City:COLUMBUS
State:OH
ZIP:43216-2219
Country:US
Phone:614-790-3333/800-274-5263
CAGE:34897

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50

ORAL RAT IS UNKNOWN.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: SEVERE EYE IRRITATION, NASAL AND RESPIRATORY TRACT IRRITATION, CENTRAL NERVOUS SYSTEM EFFECTS, POSSIBLE UNCONSCIOUSNESS, EVEN DEATH. INGESTION CAN CAUSE GASTROINTESTINAL IRRITATION. ASPIRATION INTO LUNGS AFTER INGESTION CAN CAUSE CHEMICAL PNEUMONITIS AND DEATH. CHRONIC: LIVER, KIDNEY AND BRAIN DAMAGE.

Explanation of Carcinogenicity:TOLUENE MAY BE HARMFUL TO THE FETUS BASED ON LABORATORY STUDIES.

Effects of Overexposure:EYES: BURNING, TEARING, REDNESS, SWELLING. SKIN: REDNESS, BRUNING, DRYING, CRACKING. INHALATION: DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS, DEATH. INGESTION: NAUSEA, VOMITING, DIARRHEA, AND SAME SYMPTOMS AS INHALATION.

Medical Conditions Aggravated by Exposure:PREEXISTING EYE, SKIN, CENTRAL NERVOUS SYSTEM AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. SEE DOCTOR. INHALATION: REMOVE VICTIM TO FRESH AIR. GIVE OXYGEN/CPR IF NEEDED. SEE DOCTOR. INGESTION: DO NOT INDUCE VOMITING. GIVE VEGETABLE OIL OR CHARCOAL SLURRY. IF SPONTANEOUS VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION INTO LUNGS. SEE DOCTOR IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=-7.2C, 45.F

=====
===== 45 =====

Lower Limits:1.2

Upper Limits:7.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS W

ITH WATER SPRAY.

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR. CAN TRAVEL ALONG GROUND AND FLAHSBACK. COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. VENTILATE AREA. WEAR PROPER PROTECTIVE EQUIPMENT. ABSORB IN INERT ABSORBENT AND TRANSFER TO HOOD.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED PLACE, AWAY FROM HEAT, IGNITION SOURCES AND INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:AVOID BREATHING VAPORS, AND EYE AND SKIN CONTACT. USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. EMPTY CONTAINERS RETAIN RESIDUE, TREAT THEM AS IF THEY WERE FULL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED WITH ADEQUATE VENTILATION. NIOSH/MSHA RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE APPROPRIATE FOR EXPOSURE OF CONCERN OR SCBA IF TLV IS EXCEEDED.

Ventilation:MECHANICAL (GENERAL) AND/OR LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV. USE EXPLOSION-PROOF EQUIPMENT.

Protective Gloves:NEOPRENE GLOVES.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:WORK CLOTHING TO PREVENT REPEATED OR PROLONGED SKIN CONTACT. EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. LAUNDRY CONTAMINATED CLOTHING. DISCARD CONTAMINATED LEATHER GOODS.

Supplemental Safety and Health

NEVER USE WELDING OR CUTTING TORCH NEAR THIS ITEM, BECAUSE PRODUCT, EVEN JUST RESIDUE, CAN IGNITE EXPLOSIVELY.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=111.1C, 232.F

B.P. Text:232F,111C

Vapor Pres:22 @ 68F

Vapor Density:3.2

Spec Gravity:0.872

Evaporation Rate &

; Reference:2.0 (BUTYL ACETATE = 1)

Solubility in Water:INSOLUBLE.

Appearance and Odor:CLEAR COLORLESS LIQUID. BENZENE-LIKE ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, AND
REACTIVE HYDROCARBONS (ALDEHYDES, AROMATI
CS, ETC.)

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT YOUR LOCAL ENVIRONMENTAL OFFICER.

DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND
LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this in

formation to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.