View NSN Online: https://aerobasegroup.gr/nsn/5970-00-285-0269

Product ID:SYNTHITE AC-29-7S

MSDS Date:01/01/1987

FSC:5970

NIIN:00-285-0269

MSDS Number: BDTKV === Responsible Party ===

Company Name: JOHN C. DOLPH COMPANY

Box:267

City:MONMOUTH

State:NJ

ZIP:08852-9513 Country:US

Emergency Phone Num:908-329-2333

CAGE:DO943

=== Contractor Identification ===

Company Nam

e:JOHN C DOLPH COMPANY

Box:267

City:MONMOUTH

State:NJ

ZIP:08852-9513

Country:US

Phone:908-329-2333

CAGE:81476

Company Name: JOHN C. DOLPH CO.

Address:WEST NEW RD

Box:267

City:MONMOUTH JUNCTION

State:NJ

ZIP:08852-9513 Country:US CAGE:DO943

======= Composition/Information on Ingredients ========

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000 Fraction by Wt: 28.0%

OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Q

ty:1000 LBS Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 4.0% **OSHA PEL:100 PPM** Ingred Name: N-BUTYL ALCOHOL (SARA III) CAS:71-36-3 RTECS #:EO1400000 Fraction by Wt: 5.5% **OSHA PEL:100 PPM** ACGIH TLV:S, C 50 PPM; 9293 EPA Rpt Qtv:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: INSULATING COMPOUND (BY DIFFERENCE 62.5% APPROX)PROP **FORMULA** Fraction by Wt: 62.5% ACGIH TLV:NOT SPECIFIED Ingred Name: SPECIAL NOTE FOR PIGMENTS CATALYST IN SUPPL DATA RT ECS #:9999992Z ============= Hazards Identification ======================== Effects of Overexposure: INHALATION OF HIGH CONC. MAY RESULT IN MILD DEPRESSION TO CONVULSIONS & LOSS OF CONSCIOUSNESS. First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED; EYES/SKIN: FLUSH W LG AMTS H*20 FOR 15 MIN; INGEST: RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSUR E. =========== Fire Fighting Measures ========================== Flash Point:50F (ASTM D-56) Lower Limits:0.9 **Upper Limits:6.0** Extinguishing Media: WATER MAY BE INEFFECTIVE-RECOMMEND DRY

CHEMICAL, CO*2, FOAM

Fire Fighting Procedures: USE ALL METHODS THAT ARE RECOMMENDED FOR FLAMMABLE LIQUIDS.

Unusual Fire/Explosion Hazard: KEEP AWAY FROM HEAT, FIRE AND OPEN FLAME. REMOVE EMPTY DRUM IMMEDIAT. AS VAPORS ARE EXPLOSIVE.

======== Accidental Release Measures =========

Spill Release Procedures:KEEP SOURCES OF IGNITION AWAY.RECOVER FREE LIQUID ADD ABSORBENT (SAND,EARTH,ETC.) PLACE MATERIAL IN DRUMS AND DISPOSE OF AS WASTE.
======================================

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. KEEP AWAY FROM HEAT AND OPEN FLAME.USE ONLY WITH ADEQUATE VENTILATION Other Precautions:AVOID PROLONGED OR REPEATED BREATHING OF VAPORS OR CONTACT WITH SKIN.

===== Exposure Controls/Pers onal Protection ========

Respiratory Protection: NO SPECIAL REQMNTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves: NEOPRENE

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: EYE WASH STATION. APRONS. SPECIAL IMPERVIOUS CLOTHING.

Supplemental Safety and Health

MSDS DATED 11/18/84. OTHER INGREDIENTS:-ZIRCONIUM 0.005%, COBALT NAPHTHENATE 0.0018% MANGANESE NAPHTHENATE 0.0012%

HCC:F2

Boiling Pt:B.P. Text:220-320F

Vapor Pres:7.6 Vapor Density:4.0 Spec Gravity:1.0

Evaporation Rate & Department Reference: 1.5 Solubility in Water: 2.0 MODERAT

Appearance and Odor:CLEAR AMBER COLOR-AROMATIC HYDROCARBON ODOR

Percent Volatiles by Volume:50.0

======== Stability and Reactivity Data ============

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY THE MFR Stability Condition to Avoid:HEAT AND FIRE Hazardous Decomposition Products

:CO	$\Lambda NI\Gamma$	\mathcal{L}	1*2
`(,()	AIVI	, , ,) /

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF THE COLLECTED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY IAW LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.