

KALCOR COATING CO -- 98-4981, YELLOW STENCIL PAINT -- 8010-00-285-4935

=====
Product Identification
=====

Product ID:98-4981, YELLOW STENCIL PAINT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-285-4935

MSDS Number: BDTRB

=== Responsible Party ===

Company Name:KALCOR COATING CO

Address:37721 STEVENS BLVD

City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

Info Phone Num:216-946-4700

Emergency Phone Num:216-

946-4700

CAGE:33201

=== Contractor Identification ===

Company Name:KALCOR COATING CO

Address:37721 STEVENS BLVD

Box:City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

Phone:216-946-4700

CAGE:33201

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 14.9%

OSHA PEL:100 PPM

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 1.2%

OSHA PEL:100 PPM

AC

GIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 11.3%

OSHA PEL:100 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 0.6%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:DIARYLIDE YELLOW, PIGMENT

=====
Hazards Identification
=====

=

Effects of Overexposure:AVOID SKIN/EYE CNTCT

=====
First Aid Measures
=====

First Aid:SKIN: FLUSH W/WATER. EYES: SPLASH, FLUSH W/WATER FOR 15 MIN.
INH: REMOVE TO FRESH AIR. INGEST: CALL MD IMMED.

=====
Fire Fighting Measures
=====

Flash Point:52F SCC
Extinguishing Media:CO*2, DRY CHEM, FOAM

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION
. CLEAN AS ANY
PAINT.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID EXCESS HEAT, SPARKS, OPEN FLAMES

=====
Exposure Controls/Personal Protection
=====

Ventilation:LOCAL VENT NECESSARY
Protective Gloves:REC
Eye Protection:SAFETY GLASSES OF GOGGLES
Supplemental Safety and Health
VAP DNSTY HEAVIER THAN AIR. WT/GAL 11.1 LBS. DOT: FLAMMABLE LIQ CLASS
IB.

=====
Physical/Chemical Properties
=====

=====

Boiling Pt:B.P. Text:241-385F
Spec Gravity:1.3000
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NEGLIGIBLE
Appearance and Odor:YELLOW PAINT, PETROLEUM SPIRITS ODOR
Percent Volatiles by Volume:48.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:EXCESS HEAT, SPARKS, OPEN FLAME

===== Disposal Considerations =====

Waste Disposal Methods:EPA APPRVD LANDFILL OR INCINERATION IF IAW FED,
STATE, LOCAL REG.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.