

UNOCAL CHEMICALS DIV.,UNION OIL OF CALIFORNIA -- AMSCO SOLV 1106 \* 140 SOLVENT 66/3 \* 11106 -- 6850-00-285-8011

=====  
===== Product Identification =====

Product ID:AMSCO SOLV 1106 \* 140 SOLVENT 66/3 \* 11106

MSDS Date:06/17/1987

FSC:6850

NIIN:00-285-8011

MSDS Number: BDTRZ

=== Responsible Party ===

Company Name:UNOCAL CHEMICALS DIV.,UNION OIL OF CALIFORNIA

Address:1900 E. GOLF RD.

City:SCHAUMBURG

State:IL

L

ZIP:60194-5021

Info Phone Num:312-490-2500/LA POISON213-664-2121

Emergency Phone Num:312-490-2500/CHEMTREC 800-424-9300

CAGE:94684

=== Contractor Identification ===

Company Name:PHIPPS PRODUCTS CORP

Address:186 LINCOLN ST SUITE 502

Box:City:BOSTON

State:MA

ZIP:02111-2403

Country:US

Phone:OUT OF BUSINESS

CAGE:86511

Company Name:UNOCAL CHEMICALS DIV.,UNION OIL OF CALIFORNIA

Address:1345 N MEACHAM

Box:City:SCHAUMBURG

State:IL

ZIP:60196

Phone:312-490-2500/800-424-9300(CHEMTREC)

CAGE:94684

=====

=====  
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM NAPHTHA UN1255 (ALSO IDENTIFIED BY MFR AS CAS NO 8052-41-3)

CAS:64742-47-8

Fraction by Wt: 100%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM STEL 200 PPM

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT IS IRRITATING TO BODY TISSUES.  
PROLONGED

AND/OR REPEATED BREATHING OF FUMES MAY CAUSE  
NON-REVERSABLE CENTRAL NERVOUS SYSTEM DAMAGE(PAINTERS SYNDROME).  
INTENTIONALLY CONCENTRATING & BREATHING V APORS MAY BE HARMFUL OR  
EVEN FATAL.

Effects of Overexposure:EYE:IRRITATION BY CONTACT WITH LIQUID OR VAPOR.  
SKIN:IRRITATION.PROLONGED CONTACT MAY CAUSE DRYING OR CRACKING.  
INHALED:IRRITATION AND CENTRAL NERVOUS SYSTEM DEPRESSION.  
INGESTED:G/I IRRITATION,NERVOU S SYSTEM DEPRESSION. ASPIRATION INTO  
LUNGS.

Medical Cond Ag

gravated by Exposure:PEOPLE WITH PRE-EXISTING SKIN OR  
RESPIRATORY DISORDERS MAY BE MORE SUSCEPTABLE TO THIS PRODUCT.

=====  
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER. SKIN:REMOVE CONTAMINATED CLOTHING. WASH  
WITH SOAP & WATER. INHALED:REMOVE FROM EXPOSURE. GIVE OXYGEN OR  
ARTIFICIAL RESPIRATION IF NEEDED. GET MEDICAL ATTENTION.  
INGESTED:DO NOT I NDUCE VOMITING. GET MEDICAL ATTENTION. IF  
SYMPTOMS PERSIST,GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:141F/61C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE  
WATER TO COOL FIRE EXPOSED CONTAINERS,BEING CAREFUL NOT TO SPREAD  
FIRE WITH WATER.

Unusual Fire/Explosion Hazard:MATERIAL WILL NOT IGNITE READILY,BUT CAN  
BE IGNITED BY FLAME AND WILL BURN EASILY ONCE IGNITED.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. VENTILATE AREA.  
ABSORB WITH INERT MATERIAL. STORE IN CLOSED CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE TIGHTLY CLOSED IN A  
COOL,DRY,WELL VENTILATED AREA FREE FROM IGNITION SOURCES.

Other Precautions:"EMPTY" DRUMS MAY CONTAIN SUFFICIENT RESIDUE OR VAPOR  
T

DO NOT BE EXPLOSION HAZARD. DO NOT CUT, WELD, GRIND ON "EMPTY" CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE NIOSH ORGANIC VAPOR RESPIRATOR OR SUPPLIED AIR RESPIRATOR IF EXPOSED ABOVE TLV(PEL)  
Ventilation: USE GENERAL OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(PEL)  
Protective Gloves: OIL/SOLVENT RESISTANT OR IMPERVIOUS  
Eye Protection: SAFETY GLASSES AND/OR SPLASH GOGGLES  
Other Protective Equipment: IMPERVIOUS CLOTHING (IF NEEDED TO PREVENT PROLONGED/REPEATED CONTACT). EYE WASH/SAFETY SHOWER.  
Work Hygienic Practices: USE NORMAL CHEMICAL HYGIENE PROCEDURES.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: N1  
Boiling Pt: B.P. Text: 367-405F  
Vapor Pres: NEGLIGIBLE  
Vapor Density: 5.2 (AIR)  
Spec Gravity: 0.772  
Evaporation Rate & Reference: 0.8 BUAC  
Solubility in Water: NEGLIGIBLE  
Appearance and Odor: CLEAR, ALMOST COLORLESS LIQUID, HYDROCARBON ODOR  
Percent Volatiles by Volume: 100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
STRONG ACIDS, OR BASES, OXIDIZING AGENTS, SELECTED AMINES  
Stability Condition to Avoid: NONE REPORTED. HMIS-HIGH TEMPERATURES  
Hazardous Decomposition Products: NORMAL PRODUCTS OF COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE I/A/W FEDERAL, STATE, LOCAL REGULATIONS.  
HMIS SUGGESTS INCINERATION.

Disclaimer (provi

ded with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.