

PRAXAIR INC -- 14110 GREEN -- 8010-00-286-7727

===== Product Identification =====

Product ID:14110 GREEN

MSDS Date:01/01/1985

FSC:8010

NIIN:00-286-7727

MSDS Number: BDTWS

=== Responsible Party ===

Company Name:PRAXAIR INC

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Phone Num:203-794-5782

Emergency Phone Num:203-794-5782

CAGE:0LV01

=== Contractor Identification

===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

Company Name:PRAXAIR, INC.

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06810-5113

Country:US

Phone:800-772-9247; 800-PRAXAIR

CAGE:0LV01

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 45%

ACGIH TLV:500 PPM

Ingred Name:TRIETHYLAMINE (SARA III)

CAS:121-44-8

RTECS #:YE0175000

Fraction by Wt: 0.5%

=====
===== Hazards Identification =====

Effects of Overexposure:IRRIT OF NOSE,THROAT,EYES & POSS DIZZINESS & NAUSEA.SPRAY MIST CONTN LEAD.

=====
===== First Aid Measures =====

First Aid:INHAL:REMOVE FR EXPOSUR & PROVID FRESH AIR.SPLASH EYES-FLUSH IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC VOMITNG.CONSUL T A DR . IMMED IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point:104 F 40 C TCC

Extinguishing Media:CLASS B EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL FOAM

Fire Fighting Procedures:SELF CONTAINED BREATH APPARAT WATER MAY BE INEFECTIVE.

Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTHLY CLOS.ISOLAT FR HEAT,ELECTR EQPMT,SPARKS & OPN FLAME.DO NOT APPLY TO VRYHOT SUR

=====
===== Accidental Release Measures =====

Spi

Il Release Procedures:REMOV ALL SOURCES OF IGNIT (FLAMES,HOT SURFACES,ELECTRICAL, STATIC OR FRICRTIONAL SPARKS).VENTILAT ATEA & AVOID BREATHING VAPORS.REMOV W/ INERT ABSORB & NON-SPARKING TOOLS.STEPS MUST BE TAKN TO PREVNT CONTAM OF GROUND WATR OR STREAMS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOV 120 F.STORE LG QUANTITIES IN COMPLIA W/OSHA 1910.106.CONTNRS SHLD BE GROUNDED & BONDED TO THE RECE

IVING CONTNR.

Other Precautions:DO NOT CUT OR WELD ON EMPTY CONTAINER. DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY WHN SPRAYING IN OUTDR

Ventilation:PROVID GEN DILUT/LOC EXHAUST VENT TO KP CONCENT BELO ACEP TL

Protective Gloves:SOLVENT,IMPERME

Eye Protection:SAFETY EYEW

Other Protective Equipment:PROTECTIVE EQUIPMENT TO PRVNT SKN CONTCT.SE

OSHA,29 CFR 1910.1025

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Vapor Density:>AIR

Evaporation Rate & Reference:>ETHER

Percent Volatiles by Volume:60

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTCT W/STRONG ACIDS OR AKALINE MATERIALS.

Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES.

Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE & OXIDES OF CARBON & LEAD.

Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEM W/O TECHN SUPERVISION.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/LOCAL, STATE & FEDERAL REGULATIONS.INCINERATIN EPA APPRVD FACILITY.DO NOT INCINERAT CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This i

nformation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.