

DURON,INC -- TT-E-508C 8010002867839 -- 8010-00-286-7839

=====
===== Product Identification =====

Product ID:TT-E-508C 8010002867839

MSDS Date:01/01/1985

FSC:8010

NIIN:00-286-7839

MSDS Number: BDTYF

=== Responsible Party ===

Company Name:DURON,INC

Address:10406 TUCKER ST

City:BELTSVILLE

State:MD

ZIP:20705-2201

Country:US

CAGE:HO323

=== Contractor Identification ===

Company Name:DURON INC AMERICAN DIV

A

Address:10406 TUCKER ST

Box:City:BELTSVILLE

State:MD

ZIP:20705-2201

Country:US

CAGE:55652

Company Name:DURON,INC

Address:10406 TUCKER STREET

Box:City:BELTSVILLE

State:MD

ZIP:20705

Phone:301-937-4600

CAGE:HO323

=====
===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:ALKYD RESIN,SOLIDS

Fraction by Wt: 23.1

%

Ingred Name:MINERAL SPIRITS
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 27.6%
ACGIH TLV:100 PPM

Ingred Name:SILICATES

=====
===== Hazards Identification =====

Effects of Overexposure:IRRIT OF RESPIRATORY TRACT & EYES.INHAL OF HIGH
VAP CONCENTR MAY RESULT IN DIZZINESS,HDACH & UNCONSC

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH W/WATER F/15 MIN.GET MEDICAL ATTENT.IF OVERCOME BY
VAPOR,REMOVE FR EXPOSED AR
EA.IF BREATHING IS IRREG OR STOPPED,START
RESUSCITATION.

=====
===== Fire Fighting Measures =====

Flash Point:104F 40C
Lower Limits:0.9
Extinguishing Media:USE CARBON DIOXIDE,DRY CHEMICAL OR FOAM
Fire Fighting Procedures:FIGHT LIKE A GASOLINE FLASH FIRE
Unusual Fire/Explosion Hazard:EXPOSURE TO EXTREME HEAT MAY CAUSE
BURSTING OF CLOSED CONTAINERS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITI
ON SOURCES,KEEP PEOPLE
AWAY.RECOVER LIQUID ADD ABSORBENT TO SPILL AREA.AVOID BREATHING
VAPORS.VENTILATE ENCL SPACES.KEEP PETROLEUM PRODUCTS OUT OF ALL
PUBLIC SEWER & STREAMS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS & OPEN
FLAME
Other Precautions:AVOID PROLONGED CONTACT W/SKIN. DO NOT TAKE
INTERNALLY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protec

tion:HYDROCARBON OR ORGANIC VAP
CANISTERS.SELF-CONTAIN APPARATUS ABOV TLV
Ventilation:LOC-FACE VELOCITY 60FPM
Protective Gloves:RBBER/PLASTIC
Eye Protection:SAFETY GOGG OR GLASSES
Other Protective Equipment:MUST COMPLY W/SECTION 1910.132.135 OSHA
STNDS.

Supplemental Safety and Health
HAZ.INGRED.TITANIUM DIOXIDE,SILICATES,CALCIUM CARBONATE COMBINES EQUALS
48.9%

===== Physical/Chemical Properties =====

HCC:F4
Vapor Density:HEAV
Spec Gravity:1.37
Appearance
and Odor:LIQUID PAINT-MILD ODOR
Percent Volatiles by Volume:48.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:STRONG OXIDANTS LIKE LIQUID CHLORINE &
CONCENT OXYG HI TEMP
Hazardous Decomposition Products:CARBON MONOXIDE IN THE CASE OF
INCOMPLETE COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN CLOSED DOT APPROVED CONTAINER.RAGS &
ABSORBENT MATERIAL SHOULD BE IMMED IMMERSED IN WATER USE APPRVD
LANDFILL IN ACCORDANCE W/LOCAL STATE & FEDERAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek co

mpetent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.