View NSN Online: https://aerobasegroup.gr/nsn/3439-00-288-4048

UNION CARBIDE -- ARC GOUGING ELECTRODES -- 3439-00-288-4048

======== Product Identification ============

Product ID:ARC GOUGING ELECTRODES

MSDS Date:01/01/1985

FSC:3439

NIIN:00-288-4048

MSDS Number: BDTZZ === Responsible Party ===

Company Name: UNION CARBIDE Emergency Phone Num: 304-744-3487

CAGE:07098

=== Contractor Identification === Company Name:UNION CARBIDE

Phone:800-822-4357

CAGE:07098

Company Name:UNIO N CARBIDE CORP

Address:39 OLD RIDGEBURY ROAD

Box:City:DANBURY

State:CT

ZIP:06817-0001 Country:US

Phone:800-822-4357/732-563-5522 (MSDS)

CAGE:61637

======= Composition/Information on Ingredients ========

Ingred Name: GRAPHITE, SYNTHETIC

CAS:7440-44-0

RTECS #:FF5250100 Fraction by Wt: UNK

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name: ALKALI HALIDES (FROM GROUP OF CHLORIDES, FLUORIDS, BROMIDES &

IODIDES OF SOIDUM/POTASSIUM)

Fraction by Wt: 6.0%

Ingred Name: ALKAL

I SILICATES (FROM GROUP OF COMPLEX SILICON OXIDE COMPOUNDS OF SODIUM & POTASSIUM) Fraction by Wt: 4.0% Ingred Name: COPPER (SARA III) CAS:7440-50-8 RTECS #:GL5325000 Fraction by Wt: 30.0% OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2MG/M3 FUME; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: RARE EARTH OXIDES (FROM GROUP OF COMPLEX OXIDES OF LANTHANUM, CERIUM, PRASEODYMIUM) Fraction by Wt: 20.0% =========== Hazards Identification ========================== Effects of Over exposure:POSSIBLE HAZARDS:ELECTRIC SHOCK & BURNS; RADIANT ENERGY; GASES, FUMES, & DUSTS. First Aid:ELECTRIC SHOCK & BURNS:DEACTIVATE POWDER, ADMINISTER CPR AS INDICATED, COVER BURNS W/STERILE DRY DRESSINGS. CALL A PHYSICIAN; RADIANT ENERGY: IF"FLASH" BURNS OF EYES & SKIN. SEE PHYSICIAN; GASES:REMOVE TO FRESH AIR ============ Fire Fighting Measures ========================= Extinguishing Media:WILL NOT B URN, USE WATER TO COOL Fire Fighting Procedures: NONE CURRENTLY KNOWN Unusual Fire/Explosion Hazard: NONE CURRENTLY KNOWN ============ Handling and Storage =========================== Handling and Storage Precautions: CANNOT CALSSIFY ARE GOUGING FUMES IN SIMPLE MANNER, DEPENDENT ON ALLOY & ELECTRODES USED. REVIEW OSHA ZACFR 1910.252

Other Precautions: AVOID ALLOWING ITEM TO BECOME AN IGNITION SOURCE FOR COMBUSTIBLES/FLAMMABLES

====== Exposure Controls/Personal Protection

==========

Respiratory Protection: DEPENDS ON SPECIFIC USE, CONDITIONS & LOCATION; OSHA ZACFR 1910.252

Ventilation: LOCAL EXHAUST DEPENDS ON INDIVIDUAL CIRCUMSTANCES

Protective Gloves:WELDING GLOVES

Eye Protection: SAFETY GOGGLES/SPECTACLES

Other Protective Equipment:WELDING HELMET,FLAME RETARDANT CLOTHING, EAR PROTECTION

Supplemental Safety and Health

======== Physical/Chemical Properties ==========

HCC:N1

Appearance and Odor:BARE & COPPER COATED CARBON RODS, ALL SIZES &SHAPE

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

NONE CURRENTLY KNOWN

Stability Condition to Avoid: NONE CURRENTLY KNOWN

Hazardous Decomposition Products:OZONE, COPPER OXIDE & CARBON MONOXIDE, OXIDES OF INGREDIENT

======= Disposal Considerations ===========

Waste Disposal Methods:NORMAL, ENVIRONMENTALLY ACCEPTABLE, INDUSTRIAL WASTE DISPOSAL, LAND FILL, BURIAL, ETC

Disclaimer (provided

with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.