

PHOENIX PLASTICS INC -- O-L-298B -- 6850-00-291-0963

=====
Product Identification
=====

Product ID:O-L-298B

MSDS Date:01/01/1985

FSC:6850

NIIN:00-291-0963

MSDS Number: BDVKS

=== Responsible Party ===

Company Name:PHOENIX PLASTICS INC

Address:215 S 23RD ST

City:PHOENIX

State:AZ

ZIP:85034-2503

Country:US

Emergency Phone Num:617-542-7341

CAGE:06372

=== Contractor Identification ===

Company Name:PHIPP

S PRODUCTS CORP

Address:186 LINCOLN ST SUITE 502

Box:City:BOSTON

State:MA

ZIP:02111-2403

Country:US

Phone:OUT OF BUSINESS

CAGE:86511

Company Name:PHOENIX PLASTICS INC

Address:215 S 23RD ST

Box:City:PHOENIX

State:AZ

ZIP:85034-2503

Country:US

CAGE:06372

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

Fraction by Wt: 1000%

ACGIH TLV:300 PPM

=====
Hazards Identification
=====

Effects of Overexposure:SEVERE EYE IRRITANT,

DRYING SKIN. XS

INHALE=HEADACHE, DIZZINESS & NAUSEA.

=====
First Aid Measures =====

First Aid:EYE:FLUSH W WATER. SKIN:WASH W MILD SOAP & WATER & APPLY SKIN CREAM. INHALATION:REMOVE TO FRESH AIR & CALL PHYSICIAN;APPLY ARTIFICIAL RESPIRATION IF NECESSARY.

=====
Fire Fighting Measures =====

Flash Point:102F, 39C TCC

Lower Limits:0.7

Upper Limits:6.0

Fire Fighting Procedures:WATER SPRAY, CO2, FOAM, DRY CHEM

====

=====
Accidental Release Measures =====

Spill Release Procedures:FLUSH W WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE OR HOT METAL SURFACES.

=====
Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPSRKS & OPEN FLAME. USE W ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED SKIN CONTACT.

=====
Exposure Controls/Personal Protection =====

Respiratory

Protection:SELF-ONT BREATH APPARAT IF TLV EXCEEDED.

Ventilation:LOCAL

Protective Gloves:YES

Eye Protection:YES

Other Protective Equipment:EYE BATH & SAFETY SHOWER

Supplemental Safety and Health

BP:157-193C

=====
Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:315-380

Vapor Pres:2

Vapor Density:4.9

Spec Gravity:0.766

Evaporation Rate & Reference:0.06/TOLUENE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WATER-WHITE

Percent Volatiles by Volume

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: HEAT; SPARKS, OPEN FLAME & FIRE.

Hazardous Decomposition Products: CO

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF
IN ACCORD W LOCAL, STATE OR FED REG.

Disclaimer (provided with this information by the compiling agencies):

This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.