

CHEMRAY COATINGS CORP. -- TT-E-489G WHITE ENAMEL 17875 -- 8010-00-298-2288

=====  
Product Identification  
=====

Product ID:TT-E-489G WHITE ENAMEL 17875

MSDS Date:11/09/1988

FSC:8010

NIIN:00-298-2288

MSDS Number: BDWJD

=== Responsible Party ===

Company Name:CHEMRAY COATINGS CORP.

Address:209 N. MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergency Phone Num:

CHEMTREC 800-924-9300

CAGE:OBRN9

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

Company Name:CHEMRAY COATINGS CORP.

Address:209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:800-924-9300

CAGE:OBRN9

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS-RULE 66

CAS:64475-85-0

RTECS #:PY8240000

Frac

tion by Wt: 42%  
Other REC Limits:200 PPM  
OSHA PEL:N/K  
ACGIH TLV:N/K

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Fraction by Wt: 0.25%  
Other REC Limits:N/K  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 MG/M3;DUST 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:N/K  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:HIGH VAPOR CONCENTRATIONS (OVER 1000 PPM) ARE IRRITATING TO THE EYE & RESPIRATORY TRACT. MAY CAUSE HEADACHES & DIZZINESS PROLONG SKIN CONTACT IRRITATES.  
Explanation of Carcinogenicity:LEAD:IARC-HUMAN INADEQUATE, ANIMAL SUFFICIENT .  
Effects of Overexposure:REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OCCUPATION OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH PLENTY OF POTABLE WATER FOR AT LEAST 15 MINUTES, THEN OBTAIN PROMPT MEDICAL ATTN. SKIN:REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY W/SOAP & WATR. INHALATION:REMOVE TO FRESH AIR. SUPP ORT BREATHING (GIVE O\*2/ARTIFICIAL RESPIRATION). INGESTION:DO NOT INDUCE VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:103F/39.4C  
Lower Limits:0.9  
Upper Limits:7  
Extinguishing Media:CARBON DIOXIDE, FOAM, WA

TER FOG, DRY CHEMICAL.

Fire Fighting Procedures:USE NIOSH/MSHA AIR SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED CONTAINERS W/WTR SPRAY, AVOID BREATHING VAPOR OR FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS, & OPEN FALME. ADD ABSORBENT (SAND, EARTH, SAWDUST) T O SPILL. VENTILATE AREA (OPEN WINDOWS & DOORS).IF LRGE SPILL-KEEP PROD FROM ENTERNG SEWERS & WT RCOURSE BY DIKNG.ADVISE AUTH IF PROD HAS ENTERED.

Neutralizing Agent:N/K

===== Handling and Storage =====

Handling and Storage Precautions:PROPER SHIPPING NAME-PAINT. HAZARDOUS CLASSIFICATION-COMBUSTIBLE LIQUID I.D. NO. UN1263.

Other Precautions:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

=

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATORY IN CONFINED AREA.

Ventilation:LOCAL EXHAUST:FACE VELOCITY 60FPM, MECHANICAL:USE EXPLOSION-PROOF EQUIPMNT, SPECIAL:USE ONLY W/ADEQUATE VENTILATION.

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:SPLASH GOGGLES & FACESHIELD.

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR OTHER CLOTHING TO AVOID REPEATED SKIN CONTACT.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE & KEEP CONTAINER CLOSED WHEN NOT IN USE.

Supplemental Safety and Health

% VOLT:N/K . PH:N/K .

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:308F/153C

Melt/Freeze Pt:M.P/F.P Text: