

DOW CORNING -- 200 FLUID,5 CST -- 9150-00-435-2712

===== Product Identification =====

Product ID:200 FLUID,5 CST

MSDS Date:01/20/1986

FSC:9150

NIIN:00-435-2712

MSDS Number: BDYVY

=== Responsible Party ===

Company Name:DOW CORNING

Address:SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

==

= Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:DIMETHYL SILOXANE (DOW CORNING 200)

CAS:63148-62-9

RTECS #:JT6485000

Fraction by Wt: 100%

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVEREXPOSURE.  
Effects of Overexposure:EYES:TEMPORARY DISCOMFORT;SKIN:NO ADVERSE EFFECT;  
INHALATION:NO ADVERSE EFFECTS;INGESTION:NO ADVERSE EFFECT.  
Medical Cond Aggravated by Exposure:MAY ENHANCE ALLERGIC CONDITIONS ON SOME INDIVIDUALS.

==== First Aid Measures =====

First Aid:FLUSH EYES W/PLENTY OF WATER FOR 15 MINUTES. GET MED ATTN. WASH SKIN W/SOAP & WATER.

==== Fire Fighting Measures =====

Flash Point Method:OC  
Flash Point:275F(130C)  
Extinguishing Media:WATER FOG,CO\*2,DRY CHEMICAL,FOAM.  
Fire Fighting Procedures:SELF-CONT BREATH APP,PROTECTIVE CLOTHING  
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

==== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.

==== Handling and Storage =====

Handling and Storage Precautions:USE REASONABLE CARE AND CAUTION.  
Other Precautions:TRACES OF FORMALDEHYDE AND OTHER THERMAL DECOMPOSITION PRODUCTS MAY FORM AT TEMPERATURES ABOVE 302F (150C) IN THE PRESENCE OF AIR.PROVIDE ADEQUATE VENTILATION WHEN HANDLING AT ELEVATED TEMPERATURES.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED  
Ventilation:GENERAL (MECHANICAL) RECOMMENDED.  
Protective Gloves:RUBBER  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.  
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING  
Supplemental Safety and Health

==== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>300F/149C  
Vapor Pres: