

PALMER PRODUCTS INC -- 6003,EPOXY ADHESIVE,RESIN -- 4730-00-542-3362

=====
Product Identification
=====

Product ID:6003,EPOXY ADHESIVE,RESIN

MSDS Date:01/01/1987

FSC:4730

NIIN:00-542-3362

MSDS Number: BFDMF

=== Responsible Party ===

Company Name:PALMER PRODUCTS INC

Emergency Phone Num:215-584-4241

CAGE:3A281

=== Contractor Identification ===

Company Name:PALMER INTERNATIONAL, INC.

Address:2955 S

KIPPACK PIKE

Box:City:WORCESTER

State:PA

ZIP:19490

Country:US

Phone:610-584-4241

CAGE:00933

Company Name:PALMER PRODUCTS CORP

Address:146 ST MATHEWS AVE

Box:8

City:LOUISVILLE

State:KY

ZIP:40207

Country:US

Phone:502-893-3668

CAGE:3A281

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN CAS# 25068-38-6

CAS:25068-38-6

RTECS #:KC2100000

Fraction by Wt: 50%

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 40%

OSHA

PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

=====
Hazards Identification
=====

Effects of

Overexposure:EYES:IRRIT.SKIN:IRRIT,DERMATITIS.INGEST:SLIGHTLY
TOXIC.INHAL:NO PROBLEM UNLESS HEATED.

=====
First Aid Measures
=====

First Aid:INHAL:REMOVE TO FRESH AIR.EYES:FLUSH W/ WATER FOR 15 MIN,SEE
MD.SKIN:WASH W/ SOAP & WATER.INGEST:DO NOT INDUCE VOMIT,CALL MD.

=====
Fire Fighting Measures ==
=====

Flash Point:490F,254C CC
Extinguishing Media:DRY CHEMICAL,CO*2,FOAM
Fire Fighting Procedures:WEAR SCBA
Unusual Fire/Explosion Hazard:NONE PER MFR

=====
Accidental Release Measures
=====

Spill Release Procedures:SCRAPE UP

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN CLOSED CONTAINER.
Other Precautions:NFPA HAZARD
CLASSIFICATION-HEALTH:SLIGHT,FIRE:SLIGHT,REACTIVITY:LEAST.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPR ORGANIC VAP RESP WHERE VENT IS
INADEQUATE
Ventilation:MECHANICAL EXHAUST
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYE WASH & SAFETY SHOWER
Supplemental Safety and Health
MSDS PREP:86252.PART A OF A 2 PART KIT.SPEC DATA:ASSEMBLY 2.OSHA TLV
CA.MG SILICATE:20 MPPCF.KEY1:N1

=====
Physical/Chemical Properties
=====

HCC:N

1
Spec Gravity:1.32
Evaporation Rate & Reference:N/R(PER MFR)
Solubility in Water:NIL
Appearance and Odor:WHITE PASTE
Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS,AMINES,& BASES
Hazardous Decomposition Products:CO,CO*2

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR LANDFILL IN ACCORDANCE W/
FEDERAL,STATE,& LOCAL REGULAT
IONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular
situation.