

CHEMTRONICS,INC -- ELECTRIC CONTACT,CLEANG & LUBRICATING CMPD -- 6850-00-570-9360
===== Product Identification =====

Product ID:ELECTRIC CONTACT,CLEANG & LUBRICATING CMPD

MSDS Date:01/01/1987

FSC:6850

NIIN:00-570-9360

MSDS Number: BFFPV

=== Responsible Party ===

Company Name:CHEMTRONICS,INC

Address:681 OLD WILLETS PATH

City:HAUPPAUGE

State:NY

ZIP:11787

Country:US

Info Phone Num:800-645-5244

Emerge

ncy Phone Num:800-645-5244

CAGE:LO604

=== Contractor Identification ===

Company Name:CHEMTRONICS INC

Address:8125 COBB CENTER DRIVE

Box:City:KENNESAW

State:GA

ZIP:30152

Country:US

Phone:770-424-4888/800-645-5244

CAGE:21267

Company Name:CHEMTRONICS,INC

Address:681 OLD WILLETS PATH

Box:City:HAUPPAUGE

State:NY

ZIP:11787

Country:US

Phone:800-645-5244

CAGE:LO604

===== Composition/Information on Ingredients =====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS

:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 66.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:350 PPM
ACGIH TLV:350 PPM/450STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)
CAS:75-71-8
RTECS #:PA8200000
Fraction by Wt: 32.0%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ozone Depleting Chemical:1

Ingred Name:POLY(ETHYL)SILOXANE
CAS:9016-00-6
RTECS #:TQ2690000
Fraction by Wt: 2.0%
A
CGIH TLV:NOT SPECIFIED

=====
===== Hazards Identification =====

Effects of Overexposure:LIGHT-HEADNESS,GIGINESS,NARC,CARDIAC
ARRYTHMIAS.AT HIGH CONCENTRATIONS,IF INHALED,CAN CAUSE DEATH.

=====
===== First Aid Measures =====

First Aid:SKIN:WASH W.SOAP & H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T
INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF
NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE

ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point:N/A(SEE SUP DAT)
Extinguishing Media:WATER FOG
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE IN HEAT OF
FIRE.TOXIC GAS MAY EXCAPE DURING FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA-ESPECIALLY LOW PLACES WHERE
HEAVY VAPOR MIGHT COLLE

CT.REMOVE IGNITION SOURCES.KEEP OUT OF WATER
SUPPLIES.ABSORB AND WIPE UP SMALL SPILLS.TRANSFER TO CLOSED METAL
CONTAINERS.LG SPILL:DIK E WITH COMMERCIAL OR OTHER
ABSORBENT,DISPOSE LATER

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW
FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS
CLOSED. MAINTAIN STRICT HYGIENE FOR CHEM HANDLING.
Other Precautions:NONE

=====
===== Ex
posure Controls/Personal Protection =====

Respiratory Protection:USE AIR MASKS IN HIGH CONCENTRATIONS.
Ventilation:LG AMTS RELEASED-LOCAL EXHAUST,MECHANICAL IN LOW AREAS.
Protective Gloves:IMPERVIOUS
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR
PROLONGED CONTACT.
Supplemental Safety and Health
BP RANGE:-6C-149C.VAP PRESS:DICHLORODIFLUOROETHANE-4893MM.FP FOR
POLYSILOXANE G1:500F TOC.

=====
===== Physical/Chemica
l Properties =====

HCC:V2
Boiling Pt:B.P. Text:-21F-300F
Vapor Pres:SUP
Vapor Density:6.33
Spec Gravity:1.3
Evaporation Rate & Reference:>1(REF UNKNOWN)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:COLORLESS-SLIGHT ETHEREAL ODOR.
Percent Volatiles by Volume:96

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
IN WATER-SLOW HYDROLYSIS TO CORR ACID,ALUMINUM & ITS ALLOYS.
Stability Condition to Avoid:OPEN FLAMES

,HIGH TEMPERATURES,WELDING
ARCS.

Hazardous Decomposition Products:HCL,HF,POSS CARBONYL FLUORIDES,SM AMTS
PHOSGENE,FLUOR,CHLOR.

===== Disposal Considerations =====

Waste Disposal Methods:RECLAIM BY DISTILATION.SEND TO LICENSED
RECLAIMER OR DISPOSAL CONTRACTOR.COMPLY WITH LOCAL,STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.