

VARFLEX CORPORATION -- SYNTHOLVAR SHH,120/210,302,200 -- 5970-00-577-1629

=====
Product Identification
=====

Product ID:SYNTHOLVAR SHH,120/210,302,200

MSDS Date:10/01/1985

FSC:5970

NIIN:00-577-1629

MSDS Number: BFFSY

=== Responsible Party ===

Company Name:VARFLEX CORPORATION

Address:512 WEST COURT STREET

City:ROME

State:NY

ZIP:13440

Country:US

Info Phone Num:315-336-4400

Emergency Phone Num:315-3

36-4400

CAGE:79074

=== Contractor Identification ===

Company Name:VARFLEX CORPORATION

Address:512 WEST COURT STREET

Box:City:ROME

State:NY

ZIP:13440

Country:US

Phone:315-336-4400

CAGE:79074

=====
Composition/Information on Ingredients
=====

Ingred Name:PLASTICIZED POLYVINYL CHLORIDE RESIN

Ingred Name:ADDITIVES (INCLUDES 5% PIGMENTS)

CAS:24937-78-8

Fraction by Wt: 5.5%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:N

O Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: NONE SPECIFIED BY MANUFACTURER.
CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:MATERIAL IS NOT CONSIDERED AS A
CARCINOGEN BY NTP, IARC OR OSHA

Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:IF VAPORS

FROM HIGH TEMPERATURES ARE INHALED, REMOVE TO FRESH
AIR.

=====
Fire Fighting Measures
=====

Autoignition Temp:Autoignition Temp Text:NONE

Extinguishing Media:ANY MEDIA SUITABLE FOR SURROUNDING FIRES OR WATER

Fire Fighting Procedures:NO SPECIAL REQUIREMENTS.

Unusual Fire/Explosion Hazard:HYDROGEN CHLORIDE GAS LIBERATED DURING
COMBUSTION AND AT 500F AND ABOVE.

=====
Handling and Storage
=====

Handling and Storage Prec

autions:DO NOT EXPOSE TO SUNLIGHT. STORE BELOW
70 DEG. F.

Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE REQUIRED.

Ventilation:MECHANICAL(GENERAL) RECOMMENDED.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR
PROLONGED CONTACT.

Work Hygienic Practices:WASH AND SHOWER NORMALLY AT THE END OF A
WORKDAY.

Supplemental Safety and Heal

th
NONE

===== Physical/Chemical Properties =====

HCC:N1

Decomp Temp:Decomp Text:>500F,>260C

Spec Gravity:1.19-1.41

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR PLASTIC INSULATION SLEEVING, 100 FOOT SPOOL.
NO ODOR.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

DIRECT CONTACT WITH SILVER AND COPPER UNDER CERTAIN CONDITIONS CAN
CAUSE CORROSION.

Stability

Condition to Avoid:TEMPERATURES OVER 400F.

Hazardous Decomposition Products:HYDROGEN CHLORIDE GAS IS LIBERATED
DURING COMBUSTION AND AT 500F OR HIGHER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH
LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The
United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.