

ILLINOIS BRONZE POWDER & PAINT COMPANY -- GREEN(14491) -- 8010-00-584-3154

===== Product Identification =====

Product ID:GREEN(14491)

MSDS Date:01/01/1985

FSC:8010

NIIN:00-584-3154

MSDS Number: BFGPB

=== Responsible Party ===

Company Name:ILLINOIS BRONZE POWDER & PAINT COMPANY

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Info Phone Num:312-488-8001

Emergency Ph

one Num:800-228-5635

CAGE:91794

=== Contractor Identification ===

Company Name:ILLINOIS BRONZE PAINT COMPANY

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Phone:800-228-5635

CAGE:91794

===== Composition/Information on Ingredients =====

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction by Wt: 02.5%

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTE

CS #:XS5250000  
Fraction by Wt: 20.1%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)  
CAS:75-09-2  
RTECS #:PA8050000  
Fraction by Wt: 29.3%  
OSHA PEL:500 PPM/C,1000; Z2  
ACGIH TLV:50 PPM, A2; 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:PROPELLANT(PROPANE-ISOBUTANE 50:50 MOL WT %)  
Fraction by Wt: 30.7%  
ACGIH TLV:N.A.

=====  
Hazards Identification  
=====

Effects of Ove  
reposure:SKIN,EYE,RESPIRATORY  
IRRITANT.VAPORS:HEADACHE,DIZZINESS,STAGGERING GAIT,CONFUSION,COMA

=====  
First Aid Measures  
=====

First Aid:FUMES:REMOVE TO FRESH AIR.EYES:FLUSH WITH WATER 15 MIN,SEE  
PHYSICIAN.SKIN:WIPE OFF WITH TOWEL.REMOVE REMAINDER WITH MINERAL  
SPIRITS.TURPENTINE;WASH WITH SOAP AND WATER

=====  
Fire Fighting Measures  
=====

Flash Point:-40F/-40C CC  
Extinguishing Media:CO2,DRY CHEMICAL,FOAM,WATE  
R FOG  
Fire Fighting Procedures:WEAR GOGGLES AND SELF-CONTAINED BREATHING  
APPARATUS  
Unusual Fire/Explosion Hazard:CANS WILL RUPTURE AT ABOUT 190F.BURNING  
YIELDS TOXIC FUMES

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AVOID  
BREATHING FUMES,REMOVE WITH INERT ABSORBENT

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE AT OVER 120F.STORE IN

BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS 1A FLAMMABLE LIQUIDS.

Other Precautions:DO NOT PUNCTURE.DO NOT SPRAY IN EYES

=====  
===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST OR MECHANICAL TO KEEP BELOW TLV

Protective Gloves:NONE

Eye Protection:SAFETY GOGGLES/GLASSES

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:42F/6C

Vapor Density:>1

=====  
===== Stability  
and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:HYDROGEN CHLORIDE,CARBON  
MONOXIDE,PHOSGENE

=====  
===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY.DO NOT  
INCINERATE CLOSED CONTAINERS,OR DISPOSE IN ACCORD WITH GOVERNMENT  
REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by ele

ments of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.