

3M COMPANY -- SCOTCH-GRIP(TM) 1711 RUBBER AND GASKET ADH -- 8040-00-598-8065

=====
Product Identification
=====

Product ID:SCOTCH-GRIP(TM) 1711 RUBBER AND GASKET ADH

MSDS Date:01/02/1986

FSC:8040

NIIN:00-598-8065

MSDS Number: BFHPL

=== Responsible Party ===

Company Name:3M COMPANY

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:61

2-733-1110

CAGE:76381

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====
Composition/Information on Ingredients
=====

I

ingred Name:CHLOROPRENE POLYMER

Fraction by Wt:

Other REC Limits:

OSHA PEL:

ACGIH TLV:

ingred Name:MAGNESIUM RESINATE

Fraction by Wt:

Other REC Limits:

OSHA PEL:

ACGIH TLV:

ingred Name:ANTIOXIDANT

Fraction by Wt:

Other REC Limits:

OSHA PEL:

ACGIH TLV:

ingred Name:THERMOPLASTIC RESINS

Fraction by Wt:

Other REC Limits:N/D(MFR)

OSHA PEL:

ACGIH TLV:

ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

Fraction by Wt:

Other REC Limits:N/D

OSHA PEL:15MG/M3 TDUST/5 FUME

ACGIH TLV:10MG/M3 TDUS

T; 9293

ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt:

Other REC Limits:N/D(MFR)

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

ingred Name:PETROLEUM DISTILLATE.CONTAINS 23% N-HEXANE.SEE INGREDIENT
NO 8.

CAS:8030-30-6

Fraction by Wt: 21.0%

Other REC Limits:400(PPM)

OSHA PEL:

ACGIH TLV:

ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 7.0%

Other REC Limits:50(PPM)

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 929

3

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 33.0%

Other REC Limits:100 PPM

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 1.0%

Other REC Limits:

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO

Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE CONTACT:LIQUID IRRITATING TO

EYES.CAN CAUSE TEARING,REDNESS,AND BLURRED VISION.SKIN

CONTACT:ACUTE EXPOSURE IS MIDLY IRRITATING.PROLONGED OR REPEATED

CONTACT WILL PRODUCE DEFATTING AND RESULTANT DE RMATITIS.INHAL:OF

VAPORS AT CONC EXCEEDING THE ESTABLISHED EXPOS LIMITS MAY CAUSE

RESP(SIGN & SYMPTOM OF OVEREXPOSURED).

Effects of Overexposure:HLTH HAZ(ACUTE CHRONIC):SYSTEM IRRI

TATION.SYMP

OF OVEREXPOS INCLUDE DROWINESS,LIGHT-HEADEDNESS,DIZZY,NAUSEA &

HDCH.RPTD OR EXTREME OVEREXPOSURE TO TOLUENE VAPOR OR N-HEXANE MAY

CAUSE NEVEROUS SYSTEM D AMAGE.INGEST:SWALLOWING MAY CAUSE

GASTROINESTINAL IRRITATION,NAUSEA,DIARRHEA & NERVOUS SYS

IMPAIRMENT.(SEE SUP DATA)

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH EYES IMMED W/ PLENTY OF H*20 FOR AT LEAST 15

MIN(CALL PHYS.SKIN:WASH AREA W/ SOAP & H*20.INHAL:MOVE PE

PERSON TO

FRESH AIR AT ONCE.RESTORE OR SUPPORT BREATH.BREATH DIFFICULT PERSIST.CALL PH YS.INGEST:DO NOT INDUCE VOMITING.GIVE VICTIM TWO GL OF MILK OR WATER TO DRINK,CALL PHYS IMMEDIATELY.IF SPONTANEOUS VOMITING SHOULD OCCUR.LOWER HEAD BETWEEN KNEES TO PREVENT ASPIRATION INTO LUNGS.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:-14 F;-25.56 C

Lower Limits:1.0

Upper Limits:8.0

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:FIRE FIGHTERS SHOULD BE EQUIPPED W/ SCBA WHEN FIGHTING FIRES INVOLING THIS MATERIAL(MFR).USE NIOSH/MSHA APPROVED SCBA & FULL PROCTIVE EQUIPMENT

Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE.OVERHEATED,CLOSED CONTAINERS ADJACENT TO FIRE COULD EXPLODE DUE TO PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:OBSERVE PRECAUTIONS IN ALL SECTION.EXTINGUISH ALL IGNITION SOURCES.COLLECT SPILLED MATERIAL,CLEANUP RESIDUE AND STORE IN CLOSED METAL CONTAINER.(U.S.DEPOT.OF TRANSPORTATION APPROVED IF WASTE WILL BE S HIPPED)

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS & FLAME.AVOID CONTACT W/ EYES & SKIN.AVOID PROLONGED BREATH OF VAPOR.KEEP CONTR CLOSED WHEN NOT IN USE.

Other Precautions:THE VAPORS RELEASED BY THIS PRODUCT CAN BE EASILY IGNITED.KEEP OUT OF REACH OF CHILDREN.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIAE FOR EXPOSURE OF CONCERN

Ventilation:USE ONLY IN AREAS ADEQUATELY VENT W/ ENOUGH AIR MOVEMENT TO REMOVE VAPORS & PREVENT VAPORS BUILDUP.CONSULT(SEE SUP DATA)

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:CHEMICAL WORKERS GOGGLES

Work Hygienic Practices:OBSERVE GOOD WORK HYGIENCE PRACTICES

Supplemental Safety and Health

SIGNS & SYMP OF OVEREXPOS:SOLVENT ASPIRATION

INTO THE KUNGS AS A RESULT
OF VOMITING MAY CAUSE LUNG DAMAGE. VENT: LOCAL SAFETY/HEALTH
AUTHORITIES IF ADDITIONAL GUIDANCE IS NECESSARY.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt: B.P. Text: 140F

Vapor Pres: 68F 120 MM

Vapor Density: 3.0

Spec Gravity: 0.8900

Evaporation Rate & Reference: ≥ 3.5 ETHER=1

Solubility in Water: SLIGHT

Appearance and Odor: TAN, LOW VISCOSITY LIQUID W/ STRONG SOLVENT ODOR

Percent Volatiles by Volume: 61.0%

=====

=== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZERS.

Hazardous Decomposition Products: THERMAL DECOMPOSITION OR BURNING MAY
PRODUCE CO, CO₂, HCL & OTHER CHLORINATED DECOMPOSITION PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods: COMMERCIAL INCINERATION W/ DESTRUCT & REMOVAL
EFFICIENCY $\geq 99\%$ OR RECLAMATION IS PREFERRED. INCINERATED, MORE THAN
99% OF HCL IN EXHAUST GAS SHOULD BE RE
MOVED. DISPOSE IAW LOCAL &
CURRENT EPA REGS. EPA HAZARDOUS WASTE NUMBER D001 (IGNITABLE).

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify
and
assume responsibility for the suitability of this information to their
particular situation.