View NSN Online: https://aerobasegroup.gr/nsn/8010-00-634-6703 AMERON INDUSTRIAL COATINGS DIVISION -- GRAY #36081 -- 8010-00-634-6703 Product ID:GRAY #36081 MSDS Date:01/01/1985 FSC:8010 NIIN:00-634-6703 MSDS Number: BFJPR === Responsible Party === Company Name: AMERON INDUSTRIAL COATINGS DIVISION Address: 201 N BERRY ST City:BREA State:CA ZIP:92621-3904 Country:US Info Phone Num:714-529-4597 Emergency Phone Num:714-529-4597 C AGE:09869 === Contractor Identification === Company Name: AMERON INDUSTRIAL COATINGS DIVISION Address: 201 N BERRY ST Box:City:BREA State:CA ZIP:92621-3904 Country:US Phone:714-529-4597 CAGE:09869 ======= Composition/Information on Ingredients ========

Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

Effects of Overexposure: ANESTHETIC, IRR. O

============= Hazards Identification ========================

CAS:8030-30-6

RTECS #:SE7555000 Fraction by Wt: 39.0% OSHA PEL:100 PPM

NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION
======================================
First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A PHYSICAN IF CONDITIONS PERSIST.
======================================
Flash Point:86F TCC Lower Limits:1.1 Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE
FIRES-FOAM Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE
========= Accidental Release Measures ==========
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS
=========== Handling and Storage =============
Handling and Storage Precautions:DO NOT STORE ABOVE 120 F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY Supplemental Safety and Health RESPIRATOR USE BASED ON C

F RESPIRATORY TRACT OR ACUTE

========= Physical/Chemical Properties =========
HCC:F3 Boiling Pt:B.P. Text:311-373F Vapor Density:>1 Evaporation Rate & Deference: SLOWER THAN ETHER Percent Volatiles by Volume:61.0
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES
======= Disposal Considerations ==========
Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL STATE AND

HEM CONC. AND CONDITION OF USE

Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professiona I advice to verify and assume responsibility for the suitability of this information to their particular situation.