View NSN Online: https://aerobasegroup.gr/nsn/3040-00-640-2451

RELIANCE ELECTRIC CO -- 85696 -- 6110-00-640-2451

| Product ID:85696 |
|---|
| MSDS Date:01/01/1985 |
| FSC:6110 |
| NIIN:00-640-2451 |
| MSDS Number: BFJRZ |
| === Responsible Party === |
| Company Name: RELIANCE ELECTRIC CO |
| Address:3300 10TH ST |
| City:COLUMBUS |
| State:IN |
| ZIP:47201-5503 |
| Country:US |
| CAGE:38740 |
| === Contractor Identification === |
| Company Name: RELIANCE ELECTRIC CO MASTER DIVISION |
| Address |
| :3300 10TH ST |
| Box:City:COLUMBUS |
| State:IN |
| ZIP:47201-5503 |
| Country:US |
| CAGE:38740 |
| |
| ====================================== |
| Ingred Name: ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE |
| 29CFR 1910.1101) |
| CAS:1332-21-4 |
| RTECS #:CI6475000 |
| OSHA PEL:0.2 FIBERS/CC |
| ACGIH TLV:0.5 FIBERS/CC; A1;89 |
| EPA Rpt Qty:1 LB |
| DOT Rpt Qty:1 LB |
| |
| |

Effects of Overexposure: ASBESTOS DUST IS KNOWN HUMAN CARCINOGEN. ALSO

COUGH, SHORT OF BREATH, WEAKNESS, CYANOSIS, ETC.

First Aid:SKIN:CONSULT DOCTOR FOR DERMATITIS.EYES:FLUSH WITH WATER FOLLOWED BY TREATMENTS OF OPHTHALMOLOGIST.INHALATION:CONSULT PHYSICIAN AT ONCE.

Extinguishing Media:EXTINQUISH W. AGENT SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP

Spill Release Procedures: PICK UP MATERIAL & RETURN TO CONTAINER. IF ANY BROKEN MATERIAL EXISTS, BE CAREFUL TO AVOID DUSTING CONDITIONS. PLACE BROKEN MATERIAL INTO A SEALED CONTAINER. VACUUM OR WET CLEAN ONLY. DO NOT SWEEP.

Handling and Storage Precautions: AVOID CUTTING OR GRINDING ON ITEM. AVOID ANY DUSTING CONDITIONS. MAINTAIN GOOD HOUSEKEEPING.

======= Exposure Controls

/Personal Protection =========

Respiratory Protection:NIOSH APPROVED DUST MASK AS A MINIMUM.SELF CONT APP FOR DUSTING COND Ventilation:PROVIDE GOOD LOCAL VENTILATION TO KEEP BELOW PEL. Protective Gloves:WORKING GLOVES Eye Protection:SAFETY GLASSES Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT. Supplemental Safety and Health SAFETY DATA DEVELOPED BY DGSC-STF.STORAGE CODE BASED ON FACT THAT ASBESTOS IS BOUND UP & NOT LOOSE.

HCC:T6

Appearance and Odor: ASBESTOS FIBERS IN BOUND FORM IN FRICTION LINING.

Stability Indicator/Materials to Avoid:YES NONE KNOWN Hazardous Decomposition Products:NONE KNOWN

Waste Disposal Methods:PLACE IN SEALED PLASTIC BAG OR CONTAINER.ULTIMATE DISPOSAL MUST COMPLY WITH WALL LOCAL,STATE & FED

ERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.