

ENMAR -- 726-001; PRIMER COATING GRAY 36440 -- 8010-00-664-6302

=====  
Product Identification  
=====

Product ID:726-001; PRIMER COATING GRAY 36440

MSDS Date:01/01/1985

FSC:8010

NIIN:00-664-6302

MSDS Number: BFJVV

=== Responsible Party ===

Company Name:ENMAR

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:OO111

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL

COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

Company Name:ENMAR

Address:201 N BERRY ST

Box:City:BREA

Phone:(316)-7333-1361

CAGE:OO111

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:INH:ANESTHETIC,IRRIT OF RE

SP TRACT OR ACUTE CNS  
DEPRESSN W/ HDACEH,DIZZY,UNCON,COMA.SKIN/EYE IRRITAT

=====  
First Aid Measures  
=====

First Aid:SKIN/EYES:FLUSH WITH WATER. REMOVE CONTAMINATED  
CLOTHING.INHAL:MOVE TO FRESH AIR. CALL DR.IF NEEDED.

=====  
Fire Fighting Measures  
=====

Flash Point:104F TCC

Lower Limits:1.1

Extinguishing Media:SM FIRES:CO\*2, DRY CHEM. LG FIRES:POLYMER FOAM  
PREFERRED

Fire Fighting Procedures:USE SELF-CONTANED BR  
EATHING APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPLODED TO HEAT MAY  
EXPLODE DUE TO PRESSURE BUILD-UP.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME,HOT  
SURFACES,& ELECTRICAL,STATIC,OR FRICTIONAL SPARKS).AVOID BREATHING  
VAPORS.VENTILATE AREA.REMOVE W/INERT ABSORBENT & NON-SPARKING  
TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage

Precautions:DO NOT STORE ABOVE 120F STORE LG QTY  
IN BLDG DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ DO NOT TAKE  
INTERNALLY. ADD LABEL WARNING.

Other Precautions:GROUND CONTAINERS WHEN POURING.AVOID FREE FALL IN  
EXCESS OF FEW INCHES. DO NOT FLAME CUT,BRAZE OR WELD COATED  
MATERIAL W/O APPROVED RESPIRATOR OR VENTILATION.DOT:FLAM LIQUID.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR.CLSD:AIR-LINE TYPE  
Ventila

tion:GEN DILT/LOCAL EXHST TO KEEP TLV/LE BELOW LIMIT, REMV FUME  
Protective Gloves:YES  
Eye Protection:YES, FOR SPLASH  
Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING  
Supplemental Safety and Health  
THIS PRODUCT IS A SYNTHETIC SURFACER. VAPOR PRESSURE: 3.2 ; VAPOR  
DENSITY: HEAVIER THAN AIR; WEIGHT: 10.11 LBS PER GALLON.

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:311-373F  
Vapor Pres:3.2  
Evaporation Rate & Reference:SL  
LOWER THAN ETHER  
Solubility in Water:>1  
Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER.DISPOSE IN  
ACCORDANCE W/FED.,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.