

SEAGRAVE COATINGS CORP OF VA -- VINYL RED LEAD PRIMER -- 8010-00-722-7119

=====
Product Identification
=====

Product ID:VINYL RED LEAD PRIMER

MSDS Date:01/01/1987

FSC:8010

NIIN:00-722-7119

MSDS Number: BFMLG

=== Responsible Party ===

Company Name:SEAGRAVE COATINGS CORP OF VA

Address:4030 SEAGUARD AVENUE

City:PORTSMOUTH

State:VA

ZIP:23701

Country:US

Info Phone Num:804-488-4411

Emergency Phone Num:

804-488-4411/800-424-9300 CHERMTREC

CAGE:60163

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS, SEAGUARD

Address:3560 ELM AVE.

Box:City:PORTSMOUTH

State:VA

ZIP:23704

Country:US

Phone:757-397-2223

CAGE:60163

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD TETROXIDE (RED LEAD), (OSHA PEL FROM 29CFR 1910.1025)

CAS:1314-41-6

RTECS #:OG5425000

Fraction by Wt: 2420%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

Ingred Name:METHYL ISOBU

TYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 29.0%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 25.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 4.0%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300 STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:MAY BE IRRITATING TO SKIN AND RESPIRATORY SYSTEM.

=====
===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR.CALL DR. SKIN:FLUSH WITH WATER.

=====
===== Fire Fighting Measures =====

Flash Point:22 F,-6 C TOC
Lower Limits:1.3
Extinguishing Media:DRY CHEM.,CO

*2

Unusual Fire/Explosion Hazard:VAPORS CAN TRAVEL GREAT DISTANCE AND
FLASH BACK TO ORGINAL.

===== Accidental Release Measures =====

Spill Release Procedures:FOLLOW GENERAL CLEANING PROCEDURES,SMALL
SPILLS MAY BE WASHED AWAY WITH WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY PLACE AWAY FROM
ABUSE AND OPEN FLAME.SECURE ALL SOURCES OF IGNITION.

Other Precautions:ODOR THRESHOL
D IS NOT SUFFICIENT TO WARN OF
POTENTIALLY DANGEROUS CONCENTRATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST AND MECHANICAL

Protective Gloves:YES

Eye Protection:YES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:231 F,111 C

Vapor Pres:38

Vapor Density:3.45

Spec Gravity:1.15

Evaporation Rate &

Reference:> N BU AC

Solubility in Water:NEGLIGIBLE

Appearance and Odor:ORANGE LIQUID,AROMATIC ODOR.

Percent Volatiles by Volume:59.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER,ACQUEOUS SOLUTIONS

Stability Condition to Avoid:OPEN FLAMES,UNGROUNDDED EQUIP.

===== Disposal Considerations =====

Waste Disposal Methods:RETURN UNUSED MATERIAL TO SUITABLE CONTAINER.

Disclaimer (provided with thi

s information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.