

MOBILE PAINT MFG CO INC -- MIL-P-15929 RED LEAD,COMP G,VINYL -- 8010-00-722-7119

=====
Product Identification
=====

Product ID:MIL-P-15929 RED LEAD,COMP G,VINYL

MSDS Date:01/01/1985

FSC:8010

NIIN:00-722-7119

MSDS Number: BFMLK

=== Responsible Party ===

Company Name:MOBILE PAINT MFG CO INC

Address:HAMILTON BLVD

Box:717

City:THEODORE

State:AL

ZIP:36582-9315

Country:US

CAGE:88633

=== Contractor Iden

tification ===

Company Name:MOBILE PAINT MANUFACTURING CO INC

Box:717

City:THEODORE

State:AL

ZIP:36582

Country:US

Phone:334-443-6110

CAGE:88633

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD TETROXIDE (RED LEAD), (OSHA PEL FROM 29CFR 1910.1025)

CAS:1314-41-6

RTECS #:OG5425000

Fraction by Wt: 25.3%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 28.8%

OSH

A PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 22%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 4.7%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300 STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN: IRRIT. VAPOR: NASAL & RESP
IRRIT, ASPHYXIATION. INGESTION: GI TRACT IRRIT, NAUSEA, DIARRHEA.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MINUTES, GET MED ATTN. SKIN: WASH
WITH SOAP AND WATER, REMOVE CONTAMINATE CLOTHING. INHALATION: REMOVE
TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION, CONSULT PHYSICIAN.
INGESTION: DO NOT INDUCE VOMITING, GET
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:47F/8C
Lower Limits:1.2
Extinguishing Media:CLASS B' FIRE EXTINGUISHER OR EXTINGUISHING AGENT
Fire Fighting Procedures:SELF-CONT BREATH APP, WATER FOG TO COOL EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO HEAT. OVEREXPOSURE TO DECOMPOSITION PRODUCES (SEE SUP DATA)

===== Accidental Release Measures =====

Spill Rel

ease Procedures:SECURE ALL SOURCES OF IGNITION. VENTILATE
AREA,AVOID BREATHING VAPORS. CONTAIN AND REMOVE WITH INERT
ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR HEAT,SPARKS,FLAMES
OR ABOVE F110F/43C. GROUND CONTAINER WHEN POURING,AVOID FREE FALL
IN EXCESS OF A FEW INCHES.

Other Precautions:DO NOT REUSE CONTAINER FOR OTHER PURPOSES. DO NOT
FLAME CUT,WELD OR BRAZE WITH
OUT PROPER VENTILATION OR RESPIRATORY
DEVICE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN.

Ventilation:LOCAL/MECHANICAL TO REMOVE ALL DECOMPOSITION PRODUCTS
FORMED

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:AS NEEDED TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

CTS MAY NOT BE IMMEDIATELY APPARENT,OBTAIN MEDICAL ATTENTION. CONTAINER
S

IZE: 5 GAL CAN.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:162F/72C

Vapor Density:>1

Evaporation Rate & Reference: