

BRAY OIL COMPANY, INC. -- BRAYCO 496 -- 9150-00-753-4636

=====
Product Identification
=====

Product ID:BRAYCO 496

MSDS Date:01/01/1987

FSC:9150

NIIN:00-753-4636

MSDS Number: BFNBC

=== Responsible Party ===

Company Name:BRAY OIL COMPANY, INC.

Emergency Phone Num:714-660-9414

CAGE:EO565

=== Contractor Identification ===

Company Name:BRAY OIL COMPANY, INC.

CAGE:EO565

Company Name:CASTROL INDUSTRIAL

NORTH AMERICA INC SPECIALTY PRODUCTS

DIV

Address:1001 WEST 31ST STREET

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Phone:800-621-2661/ FAX: 630-241-4140

CAGE:2R128

=====
Composition/Information on Ingredients
=====

Ingred Name:LUBRICATING OIL (PER MFR,USE 5MG/CUM AS TLV FOR OIL MIST.)

Fraction by Wt: 100%

ACGIH TLV:5MG/CUM,OILMIST

=====
Hazards Identification
=====

Effects of Overexposure:SKIN AND EYES IRRITATION.MAY CAUSE
DERMATITIS

TO SOME VERY SENSITIVE INDIVIDUALS.

=====
First Aid Measures
=====

First Aid:EYE CONTACT:FLUSH THOROUGHLY WITH WATER.CALL A
PHYSICIAN.SKIN:WASH WITH SOAP AND WATER.INGESTION:DO NOT INDUCE
VOMITING.CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:500F(C.O.C)

Extinguishing Media:DRY CHEMICAL,CO*2,FOAM,WATER FOG.

Fire Fighting Procedures:USE NIOSH APPROVED SCBA FOR FIREFIGHTING AND

IN COFINED AREA

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY THE MFR.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTIVE EQUIPMENT.STOP FLOW AND SHUT OFF SOURCES OF IGNITION.WIPE OR MOP UP OR ABSORB WITH CLAY,SAND OR SAWDUST.RECOVER IN A METAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR HEAT,OPEN FLAME OR OTHER SOURCES OF IGNITION.PROVIDE ADEQUATE VENTILATION.

Other Precautions:AVOID SKIN AND EYES CONTACT.WASH HANDS BEFORE EATING,DRINKING OR SMOKING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:PV/RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F

Spec Gravity:0.903

Solubility in Water:INSOLUBLE

Appearance and Odor:BROWN OILY LIQUID,PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE SPECIFIED

Hazardous Decomposition Products:COMBUSTION MAY PRODUCE CO AND CO*2.

=====

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES.DISPOSAL MUST BE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use

. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.