View NSN Online: https://aerobasegroup.gr/nsn/6810-00-754-2813

DOW CHEMICAL U.S.A. -- TRICHLOROETHYLENE-E -- 6810-00-754-2813

Product ID:TRICHLOROETHYLENE-E MSDS Date:01/01/1985 FSC:6810 NIIN:00-754-2813 **MSDS Number: BFNNN** === Responsible Party === Company Name: DOW CHEMICAL U.S.A. Address:2020 DOW CENTER City:MIDLAND State:MI ZIP:48640-6030 Country:US CAGE:96717 === Contractor Identification === Company Name: DOW CHEMICAL CO Address:100 LARKIN CENTER Box:City:MIDLAND State:MI ZIP:48674 Country:US Phone:800-258-2436 CAGE:96717

Ingred Name:TRICHLOROETHYLENE (SARA III) CAS:79-01-6 RTECS #:KX4550000 Fraction by Wt: >95% OSHA PEL:100 PPM/100 STEL ACGIH TLV:50 PPM/100,A5STEL;93 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:1,2-BUTYLENE OXIDE (SARA III) CAS:106-88-7 RTECS #:EK3675000 Fraction by Wt: 0.6% EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

=====

Effects of Overexposure:PROLONG/REPEATED EXPOS.TO LEVELS >100 PPM-POSSIBLE ORGANIC INJURY CAN CAUSE DEATH IF BREATHE TOO MUC

First Aid:EYES:IRRIGATE W/FLOWING WATER IMMED.& CONTIOUOUSLY FOR 15 MIN. REFER TO DR. SKIN: FLUSH WITH WATER. WASH CLOTHING BEFORE REUSE.;INHAL: REMOVE TO FRESH AIR IF EFFECTS OCCUR.; INGEST: DONOT INDUCE VOMIT . CALL DR.

=

Flash Point:NONE

Extinguishing Media:WATER FOG

Fire Fighting Procedures: PRESS. DEMANDS SELF-CONTAINES RESPIRATORY PROTECTION.

Unusual Fire/Explosion Hazard:STRONG UNPLEASANT ODOR. NOT CONSIDERED A FLAMM. LIQUID UNDER NORM. INDUSTRIAL USE CONDITIONS.

Spill Release Procedures:SMALL SPILLS: MOP,WIPE, OR SOAK UP IMMEDIATELY. REMOVE TO OUT OF DOORS.;LA RGE SPILLS:EVACUATE AREA. CONATIN LIQUID; TRANSFER TO CLOSED METAL CONTAINERS. KEEP OUT OF

WATER SUPPLY.

Handling and Storage Precautions: HANDLE W/ REASONABLE CARE. AVOID BREATHING VAPORS. STORE IN COOL PLACE. VAPORS WILL COLLECT IN LOW PLACES.

Other Precautions:HEALTH HAZ. DATA(CONTIN): ORAL RAT- LC > 4 G/KG.; EYE: PAIN & IRRIT. BUT NO(OR ONLY MINOR) CORNEAL INJURY LIKELY; SKIN ABSORPTION:VERY LOW TOXI CITY-NOT A HAZARD

Respiratory Protection:REQUIRED IN ABSENCE OF PROPER ENVIRONM. CONTROL; EMERGY:SELF-CONTN Ventilation:RECOMMENDED CONTROL OF VAPORS TO SUGGESTED GUIDE. Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES W/O S.SHLD Other Protective Equipment:NONE REQUIED. Supplemental Safety and Health NOTE: EARLIER PUBLICATIONS INDICATED THIS MATERIAL HAD EXPLOSIVE

LIMITS-THIS WAS AN ERROR IN A BASIC REFERENCE USE

D BY THE TRADE/INDUSTRY.

HCC:T4 Boiling Pt:B.P. Text:189F,87.2C Vapor Pres:60 Vapor Density:4.53 Spec Gravity:1.46 Solubility in Water:0.16/1000G Appearance and Odor:COLORLESS LIQUID. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG BASES(CAUSTIC POTASH OR SODA) Stability Condition to Avoid:AVOID OPEN FLAMES,WELDING ARCS ,OR HI-TEMP.SOURCES Hazardous Decomposition Products:HYDROGEN CHLORIDE, SMALL AMOUNTS OF

PHOSGENE/CHLO

Waste Disposal Methods:SEND SOLVENT TO A RECLAIMER. IN SOME CASES, SMALL AMTS. MAY BE TRANSPORTED TO AN AREA WHERE IT CAN BE PLACED ON THE GROUND & ALLOWED TO EVAPORATE SAFELY IF LOCAL, STATE, & FEDERAL REGUL.

Disclaimer (provided with this information by the compiling agencies): This information is for

mulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.