View NSN Online: https://aerobasegroup.gr/nsn/5330-00-776-6323

KAMAN AEROSPACE CORP. (JOHN-MANVILLE SALES CORP) -- K774684-11 ASBESTOS GASKET -- 5330-00-776-6323

Product ID:K774684-11 ASBESTOS GASKET MSDS Date:01/01/1987
FSC:5330
NIIN:00-776-6323
MSDS Number: BFNZX
=== Responsible Party ===
Company Name: KAMAN AEROSPACE CORP. (JOHN-MANVILLE SALES CORP)
Emergency Phone Num:203-242-4461
CAGE:84955
=== Contractor Identification
===
Company Name: KAMAN AEROSPACE CORP
Address:OLD WINDSOR ROAD
Box:City:BLOOMFIELD
State:CT
ZIP:06002
Country:US
Phone:203-242-4164
CAGE:84955
======================================
Ingred Name:ASBESTOS, CHRYSOTILE
CAS:12001-29-5
RTECS #:CI6478500
Fraction by Wt: >82% OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:2 FIBERS/CC; A1;9192
ACGITTEV.2 TIDERG/CC, A1,9192
======================================
Effects of Overexposure:PARTICLE MAT:IRRIT OF RESP TRACT,SKIN & EYE.
HRONIC INALATIN OF PARTICLE CAN PROD ASBESTOSIS.
======================================
First Aid:EYE:FLUSH WITH WATER 15 MINUTES,CONSULT PHYSICIAN. SKIN:FLUSH WITH WATER. INHALATION:REMOVE FROM EXPOSURE
======================================
Flash Point:NONE
Extinguishing Media: AS APPROPRIATE FOR THE SURROUNDING MATERIAL
======================================

Spill Release Procedures: EXCLUDE ALL F

ROM SPILL AREA EXCEPT TRAINED CLEAN-UP CREW. PROVIDE EXHAUST VENT WITH CAPTURE FILTRATION. DO NOT STIR UP DUST. USE WET METHOD OR APPROVED VACUUM CLEANING SYSTEM TO PICK UP SPILL. PLACE W ASTE IN DUST-TIGHT CONTAINER/PLASTIC BAG, & LABEL. Handling and Storage Precautions: STORE IN DUST TIGHT CONTAINER IN CLEAN, SECURE AREA. USE DUST SUPPRESSION CONTROL AT ALL STAGES OF HANDLING, USE AND DISPOSAL. Other Pre cautions: AVOID INHALATION OF ASBESTOS. MONITOR WORK AREAS FOR EXPOSURE LEVELS. RETAIN MEDICAL RECORDS OF WORKERS FOR AT LEAST 25 YEARS. Respiratory Protection: NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN. Ventilation:LOCAL/MECHANICAL WITH CAPTURE FILTRARTION Other Protective Equipment: BODY-COVERING WORK CLOTH, SPECIAL VACUUMING FACILITY FOR CLOT Supplemental Safety and Health UPDATE PER NON -OSHA MSDS UNDATED, RECD 2MAY85.JOHNS-MANVILLE TRADE NAME THIS MATL IS:STYLE 60:R-M K-68. HCC:T6 Boiling Pt:B.P. Text: DECOMPOSES Solubility in Water:NEGLIGIBLE Appearance and Odor:WHITE OR LIGHT GREY FIBERS. Stability Indicator/Materials to Avoid:YES

Waste Disposal Methods: DEPOSIT IN

## SECURED LANDFILL WHERE ASBESTOS WILL REMAIN BURIED. FOLLOW LOCA, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to ve rify and

assume responsibility for the suitability of this information to their particular situation.