

AMERON INDUSTRIAL COATINGS DIVISION -- 794-704 -- 8010-00-830-1822
===== Product Identification =====

Product ID:794-704
MSDS Date:01/01/1987
FSC:8010

NIIN:00-830-1822
MSDS Number: BFRPP
=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION
Emergency Phone Num:316-733-1361
CAGE:09869

=== Contractor Identification ===
Company Name:AMERON INDUSTRIAL COATINGS DIVISION
Address:20
1 N BERRY ST
Box:City:BREA
State:CA
ZIP:92621-3904
Country:US
Phone:714-529-4597
CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 3.3%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 22.0%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:50

00 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 10.5%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 19.2%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:INHALE:ANESTETIC,IRRI
TATION OF RESPIRATORY
TRACT,ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY

=====
First Aid Measures
=====

First Aid:INCASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER
WHILE REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH
AIR.CALL A PHYSICIAN IF SYMPTOMS PERSIST

=====
Fire Fighting Measures
=====

Flash Point:45F,7C TCC
Lower Limits:1.0
Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL;P
OLYMER
FOAM-LARGE FIRE
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE
FOR FIREMEN
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD UP

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT
SURFACES,AND ELECTRICAL,STATIC,OR FRICTIONAL SPARKS)AVOID BREATHING
VAPORS,VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING

TOOLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE (OR COMBUSTIBLE)LIQUID

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL WITHOUT VENTILATION

=====
===== Exposure Controls
/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY&WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING

Supplemental Safety and Health

BP 79-153C. EFFTS. OF OVEREXPOSURE-HEADACHE,DIZZINESS,ETC. OR COMA.PRIMARY IRRITATION FOR SKIN OR EYE CONTACT

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:174-308F

Evaporation Rate & Reference: