

VULCAN MATERIALS CO CHEMICALS DIVISION -- ETHYLENE DICHLORIDE -- 6810-00-838-5932
===== Product Identification =====

Product ID:ETHYLENE DICHLORIDE

MSDS Date:01/01/1985

FSC:6810

NIIN:00-838-5932

MSDS Number: BFRYK

=== Responsible Party ===

Company Name:VULCAN MATERIALS CO CHEMICALS DIVISION

Address:6200 S RIDGE RD

Box:12283

City:WICHITA

State:KS

ZIP:67277

Country:US

CAGE:24108

=== Contractor Ident

ification ===

Company Name:VULCAN MATERIALS CO CHEMICALS DIVISION

Address:6200 S RIDGE RD

Box:12283

City:WICHITA

State:KS

ZIP:67277

Country:US

CAGE:24108

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE DICHLORIDE (SARA III)

CAS:107-06-2

RTECS #:KI0525000

Fraction by Wt: 100%

OSHA PEL:50 PPM/C,100PPM

ACGIH TLV:10 PPM; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

===== Hazards Identification =====

Effects of Overexpos

ure:EYE: IRRIT,INJURY/ SKIN:DERMATITIS.

VAPORS:VOMIT,DIZZY,COMA. INGESTION: BURN THROAT MOUTH.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MIN,CONSULT PHYSICIAN. SKIN:WASH WITH SOAP & WATER,REMOVE CONTAMINATED CLOTHING. INHALATION:REMOVE FROM EXPOSURE,GIVE ARTIF RESP,CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL A PHYSICIAN.=

=====
===== Fire Fighting Measures =====

Flash Point:5

5F/12C (TCC)

Lower Limits:6.2

Upper Limits:15.9

Extinguishing Media:FOAM,CO*2,CARBON DIOXIDE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:CONCENTRATED CAN BE IGNITED BY HIGH INTENSITY HEAT SOURCE. DECOMPOSITION PROD HYD CHLORIDE

=====
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE THE AREA,VENTILATE,AVOID BREATHING VAPORS,CONTAIN SPILL. CLEAN UP AREA (WEAR PROTECTIVE CLOTHING)BY MOPPING OR WITH ABSORBENT MATERIAL, TRANSFER TO CLOSED CONTAINER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY VENTILATE AREA.

PREVENT MOIST AIR FROM ENTERING STORAGE. PIPE VENTS OUTDOORS.

Other Precautions:AVOID CONTACT WITH SKIN & BREATHING VAPORS. VAPORS ARE HEAVIER THAN AIR & WILL COLLECT IN LOW AREAS.

=====
===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL

Protective Gloves:NEOPRE

NE/VITON

Eye Protection:CHEM SAFETY GOGGLES

Supplemental Safety and Health

CONTAINER SIZE: 1 GAL BOTTLE

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:182F/83C

Vapor Pres:62

Vapor Density:3.4

Spec Gravity:1.25

Evaporation Rate & Reference:0.27(ETHER)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS CLEAR LIQUID;MILDLY SWEET ODOR.

Percent Volatiles by Volume:100

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG ALKALIES, OXIDIZING MATERIALS,
Hazardous Decomposition Products: HYDROGEN CHLORIDE, PHOSGENE

===== Disposal Considerations =====

Waste Disposal Methods: RECOVERED LIQUIDS MAY BE SENT TO A LICENSED RECLAIMER OR INCINERATED. CONTAMINATED ABSORBENT MATERIAL MUST BE DISPOSED OF IN A PERMITTED WASTE MANAGEMENT FACILITY. CONSULT LOCAL, STATE & FEDERAL DISPOSAL AUTHORITIES FOR APPROVED PROCEDURES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.