

AMERON INDUSTRIAL COATINGS DIV.,PRATT AND LAMBERT -- 789-406 -- 8010-00-842-5235

=====
Product Identification
=====

Product ID:789-406

MSDS Date:01/01/1985

FSC:8010

NIIN:00-842-5235

MSDS Number: BFSDL

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIV.,PRATT AND LAMBERT

Emergency Phone Num:316-733-1361

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL

COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD CHROMATE (VI) OXIDE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:18454-12-1

RTECS #:OF9800000

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM

/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

===== **Hazards Identification**=====

Effects of Overexposure:EYE,THROAT,SKIN,LUNG
IRRITANT;COMA;UNCONSCIOUSNESS

===== **First Aid Measures**=====

First Aid:SKIN:WASH WELL. EYES:FLUSH WITH WATER. INHAL:REMOVE TO FRESH
AIR.GIVE ARTIF.RESP.IF NEEDED,CALL MD. REMOVE CONTAMINATED
CLOTHING.

===== **Fire Fighting Measures**=====

Flash Point:40F,4C TCC

Lower Limits:0.9

Extinguishing Media:FOAM,
DRY CHEM,CARBON DIOXIDE

Fire Fighting Procedures:CLOSED CONTAINERS MAY BURST WHEN EXPOSED TO
HEAT

Unusual Fire/Explosion Hazard:AVOID FIRE,HEAT,SPARKS,IGNITION
SOURCES,STORAGE IN DIRECT SUNLIGHT.

===== **Accidental Release Measures**=====

Spill Release Procedures:VENTILATE AREA MECHANICALLY,KEEP FROM
FLAME,FIRE,SPARKS,IGNITION SOURCES;DO NOT BREATHE VAPORS;CLEAN UP
WITH ABSORBENT MATERIAL;USE NON-SPARKING TOOLS.

===== **Handling and Stor
age**=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED,UPRIGHT,AWAY
FROM FIRE,FLAME,SPARKS,IGNITION SOURCES, DIRECT SUNLIGHT;STORE
BELOW 120F.USE NFPA CLASS I FLAMMABLE STORAGE BLDG.

Other Precautions:DO NOT INGEST.GROUND CONTAINERS WHEN POURING.DO NOT
CUT,BRAZE,OR WELD COATED MATERIAL W/O APPROVED RESPRIATOR OR
VENTILATION.

===== **Exposure Controls/Personal Protection**=====

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Prote

ction:GOGGLES/GLASSES,SAFETY
Supplemental Safety and Health
CONTAINS:METHYL ETHYL KETONE(EL64750)TLV=200PPM;BUTYL
ALCOHOL(EO140)TLV=50PPM;ISOPROPLY
ALCOHOL(NT8050)TLV=400PPM;ISOBUTYL
ACETATE(AL14025)TLV=150PPM;METHYL ISOBUTYL
KETONE(SA92750)TLV=100PPM.

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:174F,78C
Appearance and Odor:LIQUID;OLIVE DRAB
Percent Volatiles by Volume:74.7

===== Stability and Reactivity Data =
=====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:LOCAL,STATE AND FED LAWS.DO NOT INCINERATE
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.