View NSN Online: https://aerobasegroup.com/nsn/8040-00-843-0802

Product ID:RTV 108, ADHESIVE SEALANT MSDS Date:04/17/1987 FSC:8040 NIIN:00-843-0802 MSDS Number: BFSFM === Responsible Party === Company Name: GENERAL ELECTRIC CO., SILICONE PRODUCT DIV. Address: HUDSON RIVER ROAD City:WATERFORD State:NY ZIP:12188 Country:US Info Phone Num:5 18-237-3330 Emergency Phone Num:518-237-3330 Preparer's Name: DA POLSINELLI CAGE:01139 === Contractor Identification === Company Name: GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT Address:260 HUDSON RIVER RD Box:City:WATERFORD

State:NY

Ingred Name:METHYLTRIACETOXYSILANE CAS:4253-34-3 RTECS #:VV4500000 Fraction by Wt: < 10% Other REC Limits:10 PPM (ACETIC AC ID) ACGIH TLV:NOT ESTABLISHED.

LD50 LC50 Mixture:LD50 ORAL RAT IS 25000 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NO HEALTH HAZARD REPORTED. Effects of Overexposure:THIS PRODUCT MAY CAUSE IRRITATION TO EYES, SKIN, NOSE, THROAT, AND RESPIRATORY SYSTEM. INGESTION MAY CAUSE STOMACH DISCOMFORT. Medical Cond Aggravated by Exposure:NONE NOTED.

First Aid:EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.IF IRRITATION PERSISTS,SEE DOCTOR. SKIN:REMOVE COMPLETELY WITH A DRY CLOTH OR PAPER TOWEL BEFORE WASHING WITH DETERGENT AND WATER. I NHALATION:REMOVE VICTIM TO FRESH AIR. INGESTION:TREAT SYMPTOMATICALLY.

Extinguishing Media:ALL STANDARD FI

REFIGHTING MEDIA.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

Spill Release Procedures:WIPE,SCRAPE OR SOAK UP IN AN INERT MATERIAL AND PUT IN A CONTAINER FOR DIS

POSAL. WASH WALKING SURFACES WITH

DETERGENT AND WATER TO REDUCE SLIPPING HAZARD. WEAR APPROPIATE PROTECTIVE EQUIPMENT DURING C LEANUP. Neutralizing Agent:NONE NOTED.

Handling and Storage Precautions: USE IN WELL VENTILATED AREA. WEAR PROTECTIVE EQUIPMENT. DO NOT BREATHE VAPORS. AVOID CONTACT WITH SKIN AND EYES.

Other Precautions:REMOVE CONTACT LENSES BEFORE USING SEALANT. DO NOT HANDLE LENSES UNTIL ALL SEALA NT HAS BEEN CLEANED FROM THE FINGERTIPS, NAILS AND CUTICLES.RESIDUAL SEALANT MAY REMAIN ON FINGER FOR SEVERAL DAYS, TRANS FER TO LENSES AND CAUSE SEVERE EYE IRRIT Respiratory Protection: NONE REQUIRED IF VENTILATION KEEPS EXPOSURE LIMITS BELOW TLV. Ventilation: USE MECHANICAL (GENERAL) VENTILATION. Protective Gloves: CLOTH GLOVES. Eve Protection:SAFETY GLASSES. Other Protective Equipment: EYE WASH STATION. Work Hygi enic Practices:WASH THOROUGHLY AFTER HANDLING. REMOVE AND LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health NONE.

HCC:N1 Spec Gravity:1.1000 Evaporation Rate & amp; Reference:< 1 (BUTYL ACETATE=1) Solubility in Water:INSOLUBLE Appearance and Odor:TRANSLUCENT PASTE. VINEGAR ODOR. Percent Volatiles by Volume:< 5

Stability Indicator /Materials to Avoid:YES NONE NOTED. Stability Condition to Avoid:NONE NOTED. Hazardous Decomposition Products:SILICON DIOXIDE AND ACETIC ACID.

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the

Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.