

PACIFIC AEROSOL,INC.2424 MERCED ST.,SAN LEANDRO CA -- 16187 -- 8010-00-852-9034

=====  
Product Identification  
=====

Product ID:16187

MSDS Date:01/01/1987

FSC:8010

NIIN:00-852-9034

MSDS Number: BFSSY

=== Responsible Party ===

Company Name:PACIFIC AEROSOL,INC.2424 MERCED ST.,SAN LEANDRO CA

Emergency Phone Num:415-351-4860

CAGE:34451

=== Contractor Identification ===

Company Name:AERVOE-PACIFIC CO, IN  
C.

Address:1198 SAWMILL RD

Box:City:GARDNERVILLE

State:NV

ZIP:89410

Country:US

Phone:(702)-782-0100

CAGE:33451

Company Name:PACIFIC AEROSOL, INC.

CAGE:34451

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 20.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 36.0%

OSHA PEL:10

00PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ALIPHATIC THINNER  
Fraction by Wt: 8.0%

Ingred Name:ISOBUTYL ALCOHOL (SARA III)  
CAS:78-83-1  
RTECS #:NP9625000  
Fraction by Wt: 18.0%  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 18.0%  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9192

==== Hazards Identification =====

Effects of Overexposure:IRRITATION OF EYES AND RESPIRATORY TRACT.  
POSSIBLE HEADACHES AND DIZZINESS.

==== First Aid Measures =====

First Aid:FUMES--MOVE AFFECTED TO FRESH AIR, RESTORE BREATHING, GET  
MEDICAL AID. EYE CONTACT--FLUSH THOROUGHLY WITH WATER, GET MEDICAL  
AID.

==== Fire Fighting Measures =====

Flash Point:-2.2F  
Lower Limits:1.0  
Extinguishing Media:CO2, DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:USE

WATER SPRAY TO COOL CLOSED CONTAINERS  
EXPOSED TO HEAT.

Unusual Fire/Explosion Hazard:KEEP FROM HEAT,SPARKS OR OPEN  
FLAME.CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT OR  
FIRE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION---VENTILATE AREA

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 120F. KEEP CONTAINERS AWAY  
FROM HEAT AND  
OPEN FLAME

Other Precautions:AVOID INHALATION OF SPRAY MIST. DO NOT TAKE  
INTERNALLY

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PAINT SPRAY MASK

Ventilation:PROVIDE VENTILATION TO KEEP VAPORS BELOW TLV

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:-10F

Vapor Density:1+

Spec Gravity:0.9

Evaporation Rate & Reference:10

Solubility in Water:NONE

=====

=== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CARBON MONOXIDE FUMES ON IGNITION

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL REGULATIONS. DO  
NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.