

VICTOREEN INC -- PN:GV3A1200 SPARK GAPS;COROTRON TUBES -- 5960-00-878-6554

=====  
Product Identification  
=====

Product ID:PN:GV3A1200 SPARK GAPS;COROTRON TUBES

MSDS Date:10/08/1991

FSC:5960

NIIN:00-878-6554

MSDS Number: BFTMX

=== Responsible Party ===

Company Name:VICTOREEN INC

Address:6000 COCHRAN RD

City:SOLOON

State:OH

ZIP:44139-3395

Country:US

Info Phone Num:216-248-9300

Emergency Phone Num:216-

248-9300

Preparer's Name:ROBERT A. JUCIUS

CAGE:63060

=== Contractor Identification ===

Company Name:VICTOREEN INC

Address:6000 COCHRAN RD

Box:City:SOLOON

State:OH

ZIP:44139-3395

Country:US

Phone:216-248-9300

CAGE:63060

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NICKEL 63, DEVICES CONTAINING QUANT OF RADIOACTIVE  
NICKEL-63,NORMAL-SOLID.

Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

LD50 LC50 Mixtu

re:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:METAL PRODUCTS IN NATURAL STATE DON'T PRESENT INHAL/INGEST/CONTACT HAZ.HOWEVER OPERATIONS SUCH AS BURN/WELD/SAW/BRAZE/FRIND MAY RELEASE FUMES/DUSTS WHICH MAY PRESENT HEALTH HAZ IF TLV EXCEEDED.RADIOACTIVE MATL IN DEVICES REPRESENT NO SIGNIFICANT RISK.MAJOR EXPO HAZ:INHAL.

Effects of Overexposure:BECAUSE OF A

MT OF NICKEL-63 CONTAINED IN

DEVICES THIS SECTION IS NOT APPLICABLE.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:NONE SPECIFIED BY MANUFACTURER. HMIS:FOLLOW AMERICAN RED CROSS 1ST AID.

=====  
===== Fire Fighting Measures =====

Autoignition Temp:Autoignition Temp Text:NP

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:USE METHODS APPLICABLE TO SURROUNDING AREA.

Fire Fighting Procedures:NICKEL-63 IN SOLID STATE PRESENT NO FIRE OR EXPLO HAZARD.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:NOT APPLICABLE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:MAX PERMISSIBLE AIR CONCEN (BASED ON 40HR WORKING WK)=3E-7 MICROCURIES/MILLILITER OF AIR.

Other Precautions:ALL TUBES CONTAIN EXEMPT QUANT OF NI63 AS DEFINED BY USNRC.BETA RAY ENERGY-67KEV,GAMMA RAYS-NONE,BETA RAY RANGE IN AIR-ABOUT 5CM(2INCHES)."PKG CONFORMS TO CONDITIONS/LIMITATIONS SPEC IN 49CFR173.422 F OR EXCEPTED RADIOACTIVE MATL,(SUPPLE)

=====  
===== Exposure Controls/Personal Protection =====

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

OTHER PRECAUT:INSTRUMENTS,ARTICLES,UN2910.

===== Physical/Chemical Properties =====

HCC:A2

NRC/State Lic Num:34-25957-01

Boiling Pt:B.P. Text:NP

Melt/Freeze Pt:M.P/F.P Text:>2300F,>126

Decomp Temp:Decomp Text:NP

Vapor Pres:NA

Vapor Density:NP

Spec Gravity:7

pH:NP

Viscosity:NP

Evaporation Rate & Reference:NP

Solubility in Water:NEGLIGIBLE.

Appearance and Odor:SOLID,GRAYISH TO BLACK PLAITING ON ANODE(S) OF DEVICES LISTED.

Percent Volatiles by Volume:NP

Corros

ion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

REACTS W/STRONG ACID TO HYDROGEN GAS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:METALLIC DUST/FUMES MAY BE PRODUCED DURING WELD/BURN/GRIND/POSSIBLY/MACHINING.REFER TO ANSI Z49.1.

===== Disposal Considerations =====

Waste Disposal Methods:NI-63 ACTIVITY PER DEVICE 0.05 TO 0.0 MICRO

CURIES.ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.DEVICES CONTAINING QUANT OF RADIOACTIVE NICKEL-63,NORMAL-SOLID.DISPO INFOR:NOT APPLICBLE-EXEMPT QUAN T.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person ut

ilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.