View NSN Online: https://aerobasegroup.gr/nsn/8010-00-900-2938

Product ID:PAINT, TRAFFIC, WHITE MSDS Date:01/01/1987 FSC:8010 NIIN:00-900-2938 MSDS Number: BFVKD === Responsible Party === Company Name: CORONADO PAINT COMPANY, INC Address:308 OLD COUNTY RD Box:308 City:EDGEWATER State:FL ZIP:32032-1812 Country:US CAGE:33200 === Contractor Identification = == Company Name: CORONADO PAINT COMPANY, INC. Address:308 OLD COUNTY ROAD Box:City:EDGEWATER State:FL ZIP:32132-1812 Country:US Phone:904-428-6461 CAGE:33200 Ingred Name: ALIPHATIC AND AROMATIC HYDROCARBONS Fraction by Wt: 16.3% ACGIH TLV:100 PPM Ingred Name: PIGMENTS Fraction by Wt: 50.4% ACGIH TLV:NO HAZARD

Ingred Name:VINYL TOLUENE BUTADIENE Fraction by Wt: 16.3% ACGIH TLV:NO HAZARD

======= Hazards Identific

Effects of Overexposure:SEVERE EYE IRRITATION. DRY SKIN. INHALATION-HEADACHE, DIZZINESS, AND NAUSEA.

First Aid:EYE CONTACT-FLUSH WITH WATER. SKIN CONTACT-WASH WITH MILD SOAP AND WATER; APPLY SKIN CREAM. INHALATION-REMOVE TO FRESH AIR AND CALL A PHYSICIAN; APPLY ARTIFICIAL RESPIRATION, IF NECESSARY.

Flash Point:53 F ;12 C. SCC Lower Limits:0.9 Upper Limits:7.0 Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:TREAT AS CLASS B FIRE. Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO RETAING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE, OR HOT METAL SURFACES.

================= Handling and Storage =

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

Respiratory Protection:SELF CONTAINED NIOSH APPROVED PROTECTION IF TLV IS EXCEEDED. Ventilation:LOCAL-YES Protective Gloves:YES Eye Protection:YES Other Protective Equipment:EYE BATH AND SAFETY SHOWER. Supplemental Safety and Health

=====

HCC:F3
Boiling Pt:B.P. Text:133 F,56 C
Vapor Pres:6
Vapor Density:3.7
Spec Gravity:1.32
Evaporation Rate & amp; Reference:1.2 BUAC
Solubility in Water:SLIGHT
Appearance and Odor:WHITE OPAQUE LIQUID, PETROLEUM DISTILLATE ODOR.
Percent Volatiles by Volume:58.5

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HEAT, SPAR KS, OPEN FLAME OR FIRE. Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE.

Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE AND SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied , warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.