

FIBER GLASS-EVERCOAT CO. -- AUTOBODY FILLER -- 8010-00-926-2133

=====
Product Identification
=====

Product ID:AUTOBODY FILLER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-926-2133

Kit Part:Y

MSDS Number: BFWTS

=== Responsible Party ===

Company Name:FIBER GLASS-EVERCOAT CO.

Address:6600 CORNELL ROAD

City:CINCINNATI

State:OH

ZIP:45242-2033

Country:US

Info Phone Num:513-489-7600

Emergency Phone Num:800-543

-4530

CAGE:LO327

=== Contractor Identification ===

Company Name:FIBER GLASS-EVERCOAT CO,INC

CAGE:LO327

Company Name:FIBRE GLASS-EVERCOAT CO INC

Address:6600 CORNELL ROAD

Box:City:CINCINNATI

State:OH

ZIP:45242

Country:US

Phone:513-489-7600

CAGE:18731

=====
Composition/Information on Ingredients
=====

Ingred Name:BENZOYL PEROXIDE (45%)

CAS:94-36-0

RTECS #:DM8575000

Fraction by Wt: 2.0%

ACGIH TLV:5 MG/CUM

Ingred Name:STYRENE, MONOMER (SARA III)

CAS:100-42-5

RTECS #:WL3675000

F

fraction by Wt: 13.0%
OSHA PEL:100 PPM
ACGIH TLV:S,50PPM/100STEL;9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TALC
RTECS #:VV7720000
Fraction by Wt: 58.0%
ACGIH TLV:20 MPPCF

Ingred Name:POLYESTER RESIN
Fraction by Wt: 27%

=====
Hazards Identification
=====

Effects of Overexposure:OBJECTIONABLE ODOR;EYE AND NASAL
IRRITATION.LOW-DIZZ&DRUNKENESS.HIGH LEVEL-ANESTHESIA

=====
First Aid Measures
=====

First Aid:
EYE&SKIN-FLUSH PROMPTLY W/PLENTY OF H₂O,GET MED
ATT.INH.-PROMPTLY REMOVE TO FRESH AIR,GET MED ATT. INGESTION-NO
KNOWN ANTIDOTE:TREAT SYMPTOMATICALLY,GET MEDICAL
ATTENTION.SKIN-REMOVE CONTAMINATED CLO THING.WASH W/SOAP & WATER.

=====
Fire Fighting Measures
=====

Flash Point:98 F CC
Extinguishing Media:WATER FOG,FOAM,CO₂,DRY CHEMICAL
Unusual Fire/Explosion Hazard:AT ELEVATED TEMP,SUCH AS FIRE
CONDITIONS,POLYMERIZATION MAY TAKE PLACE.CONTAINED
D POSS.VIOLENT
RUPTURE

=====
Accidental Release Measures
=====

Spill Release Procedures:COVER SPILL W/ABSORBENT AGENT. SCRAPE UP,CLEAN
SPILL AREA W/SOLVENT

=====
Handling and Storage
=====

Handling and Storage Precautions:CONTROL TEMPERATURE IN STORAGE BELOW
80F. DO NOT USE NEAR FIRE OR FLAMES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTIVE

OR PARTICULAR

EXPOSURE OF CONCERN

Ventilation:MECHANICAL(GENERAL)-DOWN DRAFT MECH EXHST. NO LOCAL NEEDED

Protective Gloves:NEOPRENE,NONSOL

Eye Protection:CHEM WORKERS GOGGLES

Supplemental Safety and Health

VAPOR IS 1.1 TIMES HEAVIER,THAN AIR.AT 100 F AND HAS ANS IGNITION

TEMPERATURE OF 914F CONFORMS TO SPEC TT-F-322D, AMEND

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:293 F

Vapor Pres:4.5

Vapor Density:3.6

Spec Gravity:1.74

Solubility

in Water:NEGLIGIBLE

Appearance and Odor:GRAY PASTE, AROMATIC ODOR

Percent Volatiles by Volume:12.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ORGANIC PEROXIDES

Stability Condition to Avoid:DO NOT STORE AT TEMPERATURES ABOVE 80F

Hazardous Decomposition Products:CO & CO*2

Conditions to Avoid Polymerization:DO NOT STORE AT TEMPERATURES ABOVE
80F

===== Disposal Considerations =====

Waste Disp

osal Methods:INCINERATE IN PROPERLY DESIGNED FURNACE.COMPLY
W/FEDERAL,STATE,&LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to v

erify and
assume responsibility for the suitability of this information to their
particular situation.