

AMERICAN GAS AND CHEMICAL COMPANY,LTD -- LEAK-TEC 16OX -- 6850-00-935-4068

=====
Product Identification
=====

Product ID:LEAK-TEC 16OX

MSDS Date:03/07/1995

FSC:6850

NIIN:00-935-4068

MSDS Number: BFXPJ

=== Responsible Party ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Info Phone Num:800-526-1008

Emergency Phone

Num:201-767-7300

Preparer's Name:ELENA FROST, SR CHEMIST

CAGE:03530

=== Contractor Identification ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Phone:201-767-7300

CAGE:03530

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

=====
Composition/Information on Ingredients
=====

Ingred Name:THE M

ANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE PRESENT IN THIS PRODUCT.

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL:NOT CONSIDERED LIKELY. REMOVE FROM AREA. SKIN:MILD IRRIT. EYE:MILD IRRIT. INGEST:NO PROBLEM ANTICIPATED OTHER THAN IRRIT. EFFECTS OF OVEREXPO:NONE REPORTED.

Exp
lanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NONE REPORTED.
Effects of Overexposure:SKIN/EYE IRRITATION. INGESTION:IRRITATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. FLUSH UNDER LIDS BY LIFTING THEM OR ROLLING EYES. SEE DOCTOR ASAP.
SKIN: FLUSH WITH WATER. REMOVE CLOTHING AND CONTINUE FLUSHING.
INHALATION : R
EMOVE TO FRESH AIR AND RESTORE BREATHING. GET MEDICAL HELP. INGESTION: INDUCE VOMITING. CALL PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:USE ANYSUITABLE FOR SURROUNDING MATERIAL.
Fire Fighting Procedures:USE WATER TO COOL FIRE-EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
===== Accidental Release Measures =====

Spill
Release Procedures:FLUSH W/WATER TO SANITARY SEWER SYSTEM.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID REPEATED OR PROLONGED CONTACT W/SKIN. DO NOT GET IN EYES. STORE IN COOL, DRY AREA. KEEP CONTAINERS CLOSED & PALINLY LABELED. SHELF LIFE:2YRS.
Other Precautions:AEROSOL:STORE IN COOL DRY PLACE AT TEMPERATURES BELOW 120F. DO NOT PUNCTURE OR INCINERATE AEROSOL CANS. LOW H

AZ FOR USUAL

INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:NONE SPECIFIED BY MANUFACTURER.

Eye Protection:NONE SPECIFIED BY MANUFACTURER.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AFTER HANDLING.

Supplemental Safety and Health

FORMULA CHANGED. FOR

PREVIOUS FORMULATION, SEE PNI A, SAME NSN.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:17.5

Vapor Density:>1

Spec Gravity:1.00-1.02

pH:6-7.5

Evaporation Rate & Reference: