View NSN Online: https://aerobasegroup.com/nsn/8030-00-936-9940

3M COMPANY -- SCOTCHAL BRAND EDGE SEALER 3950 -- 8030-00-936-9940

======== Product Identification ===========

Product ID:SCOTCHAL BRAND EDGE SEALER 3950

MSDS Date:01/01/1985

FSC:8030

NIIN:00-936-9940

MSDS Number: BFYFN === Responsible Party === Company Name:3M COMPANY

Address:3M CENTER

City:ST. PAUL State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:76381

=== Contractor Identification ===

Company Name: 3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR Box:City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name: MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

======= Composition/Information on Ingredients ========

Ingred Name: XYLENES (O-

ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS ========== Hazards Identification =============== Effects of Overexposure:LIQUID:IRRITATING TO EYES& SKIN.VAPORS: IRRITATIANG TO EYES AND RESPIRATORY SYSTEM. First Aid:EYE:FLUSH IMMEDIATELY W/PLENTY OF WATER. OBTAIN MEDICAL ATTN. SKIN:WASH W/ SOAP & WATER. INHALATION: PROVIDE FRESH AIR. ============ Fire Fighting Measures ========================= Flash Point:66F, L9C CC Extinguishing Media: CO2, FOAM, DRY CHEMICAL Fire Fighting Procedures: NONE REQUIRED ======== Accidental Release Measures ============ Spill Release Procedures: COLLECT SPILLED MATERIAL. CLEAN UP RESIDUE ============= Handling and Storage ========================== Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS & FLAMES. AVOID EYE & PROLONGED SKIN CONTACT. AVOID BREATHING OF VAPORS. KEEP CONTAINER CLOSED. Other Precautions: USE ONLY IN AREAS SUFFICIENTLY VETILATED TO MAINTAIN SLVENT CONCENTRATIONS BEOW TLV. ===== Exposure Controls/Personal Protection ======== Ventilation:MFG RECOM LOCAL EXHAUST Protective Gloves: MAY BE NEEDED Eye Protection: RECOMMENDED Other Protective Equipment: SAFETY SHOWER & EYE BATH Supplemental Safety and Health SOLUBILITY IN WATER:LOW;% VOLATILE BY WEIGHT: 45-5

,M-,P- ISOMERS) (SARA III)

OSHA PEL:100 PPM/150 STEL

CAS:1330-20-7

RTECS #:ZE2100000

======= Disposal Considerations ===========

Waste Disposal Methods:DO NOT LANDFILL.MFG RECM INCINERATION, IF IN ACCORDANCEW/FED, STATE & LOCAL CODES.

Discla

imer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.